

CTL610

Ultimate Universal Line Voltage Track Fixture

Specifications/Features

Fixture

Low profile side swivel design with modular component flexibility, Shade options provide a number of light control and style combinations. Can also be used as a bare lamp holder.

"Sure-Set" swivel for precise aiming.

Molded of durable Lexan™ 940.

Integral ON/OFF switch and track polarity indicator are standard.

Lamp

CTL610: (1) 150W PAR38, E26 Medium Skirted Base

CTL610/LA620: (1) 50W PAR20, E26 Medium Skirted Base

CTL610/LA630: (1) 75W PAR30 Short Neck, E26 Medium Skirted Base

CTL610/LA638: (1) 60W or 75W PAR 16, (1) 50W PAR20 or (1) 150W PAR38, E26 Medium Skirted Base

CTL610/LA6838: (1) 150W PAR38, E26 Medium Skirted Base

Warranty

This fixture is covered by ConTech's full one (1) year replacement guarantee after date of purchase.

Listing

cULus listed. Suitable for dry locations.

Fixture Compatibility

Standard ConTech track fixtures are cCSAus certified as-is for use with ConTech's many track systems, as well as with Juno®¹ Lighting track. By changing the prefix in the part number, ConTech can install inserts which make our fixtures compatible with other manufacturers. Replace "CTL" with "HTL" for Halo®² track, "LTL" for Lightolier®³ track, and "PTL" for Capri®⁴ track. For more information, please consult our factory.

Ordering Information

Example Order: -

Fixture	Finish	Lampshade	Black Accessory Clips	Accessories
<input type="text" value="CTL610"/>	<input type="text" value="B - Black
P - White
S - Silver"/>	<input type="text" value="LA620-(B,P,S) - PAR20 Shade
LA630-(B,P,S) - PAR30 Shade
LA6838-(B,P,S) - PAR38 Shade
LA638-(B,P,S) - Lamp Collar for PAR16, PAR20 or PAR38 lamps"/>	<input type="text" value="FA-37 - For use with LA620 Shade
FA-37A - For use with LA630 Shade
FA-37B - For use with LA6838 Shade"/>	<input dia.="" for="" glass="" la620="" lenses="" shade<br="" tempered="" type="text" use="" value="LF20-*86MM *(A, B, CL, G, LB, R, RO, Y, 73, LS, SL, UV) 3-3/4" with=""/> LF30-(A, B, CL, G, LB, R, RO, Y, 73, LS, SL, UV) 4-11/16" Dia. Tempered Glass Lenses for use with LA630 Shade LA-38-(B,P,S) - Egg-Crate Louver for use with LA630 Shade LF40-(A, B, CL, G, LB, R, RO, Y, 73, LS, SL, UV) 5-7/16" Dia. Tempered Glass Lenses for use with LA6838 Shade LA-39-(B,P,S) - Egg-Crate Louver for use with LA6838 Shade"/>



DIMENSIONS			
Model	A	B	C
CTL610	2-3/4"	2-1/4"	4-7/8"
CTL610/LA620	4-1/2"	3-1/2"	6-1/2"
CTL610/LA630	4-3/4"	4-3/4"	7"
CTL610/LA638	3-3/4"	2-1/4"	5-3/4"
CTL610/LA6838	6-7/8"	5-7/8"	9"

1. Juno is a registered trademark of Juno Lighting
2. Halo is a registered trademark of Cooper Lighting
3. Lightolier is a registered trademark of Philips Lighting
4. Capri is a registered trademark of Philips Lighting

Color/Pattern Legend: -A (Amber), -B (Blue), -CL (Clear), -G (Green), -LB (Light Blue), -R (Red), -RO (Rose), -Y (Yellow), -73 (Spread Lens), -LS (Linear Spread Lens), -SL (Soft Light), -UV (Optix UV Filter)