

# WAND 20 Linear



## Ordering Information

WG-WAND	MM	S	31	M		S	OD	W
Model	Fixation	Type	Length	Power <sup>1</sup>	CRI/CCT <sup>2</sup>	Driver <sup>3</sup>	Lens	Finish
WG-WAND	MM	S	31	M	930 935	S	OD (std)	W (std)

### Luminaire

- Standard Opal Diffuser for even illumination and no LED appearance.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- White finish standard.
- On / Off switch with 118" cable and plug, standard.

### Fixation

- MM = Magnetic mounting

### Type

- S = Straight run

### Length

- 31 = 31"

(Total length includes 1" for switch, requires 1" clearance for cable)

### Power<sup>1</sup>

- M = 6.4W/ft mid power (24V)

### CRI/CCT<sup>2</sup>

90+ CRI (Mid Power)

- 930 = 3000K (359 lm/ft)
- 935 = 3500K (366 lm/ft)

### Driver (remote)<sup>3</sup>

- S = Standard non-dim driver

### Lens

- OD = Satin opal diffuser (standard)

### Finish

- W = White, 20% gloss, RAL9010 (standard)

1 Wattage shown does not include power supplies/drivers.

2 Delivered lumens with opal diffuser shown.

3 24V fixture supplied complete with individual socket mount power supply 120-240V, 50-60 Hz and feed cable.

