Gude

Project: Type:



Downlights | 1 x powerLED 1.5 W | CRI 80 | 3500K | General Lighting | Chrome | Dry location | 500mA



LL-E87330-T-00







Technical data			
Туре	Semi-recessed		
Installation position	Ceiling		
Installation environment	Indoor		
Light Source	LED		
Optics	General Lighting		
Power	1.5 W		
Operation	500mA		
Source lumens	143 lm		
CCT	3500 K		
Color rendering index	80 Ra		
Safety class	Class 2		
IP	IP54		
Glow wire test	850°		
Direct mounting on normally flammable surfaces	Yes		
CE	Yes		
ETL	Yes		
Dimmable article	DALI - 1-10V		
Directional	No		
Tilting	No		
Walk-over	No		
Drive-over	No		
Cable included	Yes		
Cable length	0.39 ft		
Resin potting	No		
Type of light emission	Single emission		
Net weight	0.13 lbs		
Electrostatic discharge protection	No		
Surge protection	No		
Ordinary temperature on the glass	104 °F		

Finishing casi	ng		
Material	Brass		
Color	chrome		
Process	Electroplating		
Finishing diffu	ser		
Material	Glass		
Color	transparent		

Notes:			

Gude



Downlights | 1 x powerLED 1.5 W | CRI 80 | 3500K | General Lighting | Chrome | Dry location | 500mA

LL-E87330-T-00

Single emission downlights for indoor application. The 3500 LED light source with a general lighting light distribution is composed of 1 powerled LEDs with CCT of 3500 K and a CRI 80; the source luminous flux is 143 lm, with a 95.3 lm/W nominal luminous efficacy.

The device body is made of brass and features a chrome finish, processed by means of electroplating; the diffuser is made of glass. The ingress protection degree is IP54; the total weight is of 0.126 lbs.

The total absorbed power is 1.5 W. The power supply cable is included and features a 0.394 ft lenght.

and can be ceiling-mounted, with a 0.591 in diameter hole (in plasterboard) with an outer casing, code E84917(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class E.

Led features	
Source lumens	143 lm
Color temperature	3500 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Color rendering index	80 Ra
LED Life / Failure Ratio	
L70 B10 C0 197960h (at Tj 60 Ta 25)	

Gude



Gude | Downlights | Accessories **LL-E87330-T-00**



Outer casing - nickel

Type of installation: masonry L=3.15in, H=2.36in, D=2.36in

Code

E84917