
	0
on 24V 🧲	
ıti	tion 24V



Technical data	
Туре	LED Strip
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	48 W
Operation	24V
Source lumens	3350 lm
Voltage	24V
Frequency	50-60 Hz
ССТ	2700 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Resin potting	No
Type of light emission	Single emission
Net weight	0.28 lbs
Electrostatic discharge protection	No
Surge protection	No

Notes:

LED Strip | topLED 48 W | CRI 80 | 2700K | General Lighting | Dry location | 24V E98880

Single emission led strip for indoor application. The super warm LED light source with a general lighting light distribution is composed of 1 stripled LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 3350 lm, with a 69.8 lm/W nominal luminous efficacy.

The ingress protection degree is IP20; the total weight is of 0.276 lbs.

The total absorbed power is 48 W. The power supply cable is included and features.

and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Led features	
Source lumens	3350 lm
Color temperature	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Color rendering index	80 Ra

Ribbon

Ribbon | LED Strip | Accessories E98880

Diffuser	Code E98941
Diffuser	Code E98942
Diffuser	Code E98943
Diffuser	Code E98930
Diffuser	Code E98898
Diffuser	Code E98899
Diffuser	Code E98900
Diffuser	Code E98917

Ribbon

Ribbon | LED Strip | Accessories **E98880**

Diffuser	Code E98938
Diffuser	Code E98395
Diffuser	Code E98886
 Diffuser	Code E98887
Diffuser	Code E98888
Diffuser	Code E98909
Diffuser	Code E98913