Dronner	Project:	^
Порреі	Туре:	

#### LED Strip | 5 topLED 48 W DC 24 V | 9.6 W/m | 722 Lm/m E98572W





Technical data	
Туре	LED Strip
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Light emission direction	frontal
Power	48 W
Operation	24V
Source lumens	3610 lm
Voltage	24V
ССТ	3000 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP50
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1.64 ft
Resin potting	No
Type of light emission	Single emission
Electrostatic discharge protection	No
Surge protection	No

# 0.1

#### Notes:

### Dropper

F <sup>A</sup> G

#### LED Strip | 5 topLED 48 W DC 24 V | 9.6 W/m | 722 Lm/m E98572W

Single emission led strip for indoor application. The warm white LED light source is composed of 5 stripled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 3610 lm, with a 75.2 lm/W nominal luminous efficacy.

The ingress protection degree is IP50; the total weight is of 0 lbs.

The total absorbed power is 48 W. The power supply cable is included and features a 1.64 ft lenght.

and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains 5 light sources of energy efficiency class F.

Led features		
Source lumens	3610 lm	
Color temperature	3000 K	
Color rendering index	80 Ra	

## Dropper

#### Dropper | LED Strip | Accessories E98572W

	Fixing kit	<b>Code</b> LED-EKIT031
19 19 19 19 19 19 19 19 19 19 19 19 19 1	Fixing kit	<b>Code</b> <u>E98063</u>
	Fixing kit	<b>Code</b> <u>E98064</u>
199 199 199	Fixing kit	<b>Code</b> E98065
	Fixing kit	<b>Code</b> E98439
	Profile	<b>Code</b> E98061
	Profile	<b>Code</b> E98066
	Diffuser	<b>Code</b> E98062

## Dropper

#### Dropper | LED Strip | Accessories E98572W

Diffuser	<b>Code</b> E98941
Diffuser	<b>Code</b> E98942
Diffuser	Code E98943
Diffuser	<b>Code</b> E98930
Diffuser	<b>Code</b> E98898
Diffuser	<b>Code</b> E98899
Diffuser	<b>Code</b> E98900
 Diffuser	<b>Code</b> E98917

Diffuser	<b>Code</b> E98421
Cable and connector Length 39.37 in; insulation single; ; cable gland: no; colors: black - red.	<b>Code</b> E89123
Cable and connector Length 118.11 in; insulation single; ; cable gland: no; colors: black - red.	<b>Code</b> E89125
Cable and connector Length 11.81 in; insulation single; ; cable gland: no; colors: black - red.	<b>Code</b> E89121
Multiple socket	<b>Code</b> E89119