

BL flexFORM

Flexible, Linear LED Strip Lighting
Monochromatic, 24VDC, Constant Voltage

D2 Series

Printed



Certification



Lighting



Lamp	LED, SMD 3528, 36 Diodes/FT
CRI	90+
Load	2.6 - 3.4W/FT
Beam Angle	120°
Average Life	50,000 Hours
Lumens	236 lm/FT (4k)
Efficacy	91 lm/W (4k)

Electrical

Control	0-10V, MLV Dimming
Input Voltage	24VDC
Max Input Current	5A
Connections	20AWG, Copper Conductors
Operating Temperature	-4°F to 104°F (-20°C to 40°C)
Circuit	Class 2

Mechanical

Housing Construction	Flexible PCB Board, Silicone Jacket
Cutting Increments	1 - 15/16" (5cm)
Maximum Run Length	32' - 8" (10M), Except Blue (29')
Environmental	IP20, IP65, IP68
Mounting	Clip, Adhesive, Double Sided Tape Compatible with BL flexFORM Series

Accessories

BL flexFORM D2 TK	Termination Kit, Factory Installed
BL flexFORM D2 JC	Jumper Cable, Factory Installed

PROJECT

CLIENT

TYPE

Solid State Lighting is sensitive to power fluctuations
Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure
Lack of surge protection may void your warranty

For more information, please download the
BL LIGHTING catalogue

BL LIGHTING. ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-604-874-4405 F: 1-604-321-0445 E: info@bllighting.com
Copyright © 2017 BL INNOVATIVE LIGHTING. All Rights Reserved.

bllighting.com



BL flexFORM

Flexible, Linear LED Strip Lighting
Monochromatic, 24VDC, Constant Voltage

D2 Series

Printed

Performance

CCT/Color	Load	Lumens	Efficacy
2000K	3.50 W/FT	149 lm/FT	42 lm/W
2400K	2.60 W/FT	162 lm/FT	62 lm/W
2700K	2.60 W/FT	179 lm/FT	69 lm/W
3000K	2.60 W/FT	209 lm/FT	80 lm/W
3500K	2.93 W/FT	250 lm/FT	85 lm/W
4000K	2.60 W/FT	236 lm/FT	91 lm/W
5500K	3.00 W/FT	227 lm/FT	76 lm/W
Red	3.10 W/FT	15 lm/FT	5 lm/W
Green	3.30 W/FT	57 lm/FT	17 lm/W
Blue	3.40 W/FT	18 lm/FT	5 lm/W
Amber	2.80 W/FT	25 lm/FT	9 lm/W

Ordering

Series

BL flexFORM D2

CCT/Color*

20 = 2000K
24 = 2400K
27 = 2700K
30 = 3000K
35 = 3500K
40 = 4000K
55 = 5500K
RD = Red
GN = Green
BE = Blue
AR = Amber


Ingress Protection*

20 = IP20
65 = IP65
68 = IP68


* IP20 and IP68 colors are available only in 3K and 4K

Dimensions

IP20



IP65, IP68



PROJECT

CLIENT

TYPE

Solid State Lighting is sensitive to power fluctuations
Surge protection is highly recommended for all LED lighting products and should be on a designated circuit to protect against premature failure
Lack of surge protection may void your warranty

For more information, please download the
BL LIGHTING catalogue

BL LIGHTING. ILLUMINATE EVERYTHING

111 - 8838 Heather St. Vancouver, BC, Canada. V6P 3S8
P: 1-604-874-4405 F: 1-604-321-0445 E: info@bllighting.com
Copyright © 2017 BL INNOVATIVE LIGHTING. All Rights Reserved.

bllighting.com

