

ACRYLIC FABRIC SINGLE DRUM - SURFACE



LED MODULE

- Samsung LED
- Static 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

CONSTRUCTION

18 GA steel chassis

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

Surface

**ADDITIONAL SHADE DIMENSIONS CAN BE FOUND ON THE NEXT PAGE

BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #
EXAMPLE CATALOG # FD-18-S-L/SV4-34A18-30-9/CCK-SV4-S

STYLE	SIZE	SHAPE	FINISH	LIGHT SOURCE	WATTAGE	COLOR TEMP.	CRI
<input type="checkbox"/> FD	<input type="checkbox"/> 18	<input type="checkbox"/> S Single	<input type="checkbox"/> L White Linen <input type="checkbox"/> WA White Acrylic <input type="checkbox"/> O Oatmeal <input type="checkbox"/> HG Heathered Gray	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A18 34 Watt A Series LED <input type="checkbox"/> 40D18 40 Watt D Series LED <input type="checkbox"/> 20D18 24 Watt D Series LED	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90
<input type="checkbox"/> FD	<input type="checkbox"/> 24 <input type="checkbox"/> 36	<input type="checkbox"/> S Single	<input type="checkbox"/> L White Linen <input type="checkbox"/> WA White Acrylic <input type="checkbox"/> O Oatmeal <input type="checkbox"/> HG Heathered Gray	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A24 34 Watt A Series LED <input type="checkbox"/> 40D24 40 Watt D Series LED <input type="checkbox"/> 62D24 62 Watt D Series LED	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90

OPTIONAL EMERGENCY BACKUP (FIELD INSTALLED)

- CHA-EM-ITA Yes
- (blank) No

ACRYLIC FABRIC SINGLE DRUM - SURFACE



LED MODULE

- Samsung LED
- Static 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

CONSTRUCTION

18 GA steel chassis

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

Surface

ADDITIONAL SHADE DIMENSIONS

