

COMPRESSED FABRIC DRUM - SURFACE OR SUSPENDED



SHOWN AS SUSPENDED

LED MODULE

- Static 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable 120V TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

SHADE

Poly cotton blend (kona finishes 100% cotton) laminated to styrene

CONSTRUCTION

18 GA steel chassis

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

- Surface
 - Cable (3 cable system, 50" adjustable)
 - Stem Mounting (25" stem, 45 degree swivel)
- *** Contact Factory for custom pendant lengths

**ADDITIONAL SHADE DIMENSIONS CAN BE FOUND ON THE NEXT PAGE

BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #
EXAMPLE CATALOG # FS-18X9R-K-SV4/SV4-34A18-30-90/CCK-SV4-S

STYLE	SHAPE	MATERIAL				LIGHT SOURCE	LIGHT SOURCE	WATTAGE	COLOR TEMP.	CRI										
<input type="checkbox"/> FS	<input type="checkbox"/> 18X9R	<input type="checkbox"/> K Kraft	<input type="checkbox"/> LW Linda White	<input type="checkbox"/> LP Linda Parchment	<input type="checkbox"/> CH Cream Homespun	<input type="checkbox"/> KN Kona Navy	<input type="checkbox"/> RR Roja Red	<input type="checkbox"/> KB Kona Brown	<input type="checkbox"/> OD Olive Drab	<input type="checkbox"/> NB Natural Burlap	<input type="checkbox"/> CW Camelot Wheat	<input type="checkbox"/> CT Camelot Tusah	<input type="checkbox"/> MB Mystic Black	<input type="checkbox"/> SV4	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A18 34 Watt A Series LED	<input type="checkbox"/> 30 3000K	<input type="checkbox"/> 35 3500K	<input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90
<input type="checkbox"/> FS	<input type="checkbox"/> 24X12R <input type="checkbox"/> 36X18R <input type="checkbox"/> 48X24R	<input type="checkbox"/> K Kraft	<input type="checkbox"/> LW Linda White	<input type="checkbox"/> LP Linda Parchment	<input type="checkbox"/> CH Cream Homespun	<input type="checkbox"/> KN Kona Navy	<input type="checkbox"/> RR Roja Red	<input type="checkbox"/> KB Kona Brown	<input type="checkbox"/> OD Olive Drab	<input type="checkbox"/> NB Natural Burlap	<input type="checkbox"/> CW Camelot Wheat	<input type="checkbox"/> CT Camelot Tusah	<input type="checkbox"/> MB Mystic Black	<input type="checkbox"/> SV4	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A24 34 Watt A Series LED	<input type="checkbox"/> 30 3000K	<input type="checkbox"/> 35 3500K	<input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90
																<input type="checkbox"/> 40D18 40 Watt D Series LED				
																<input type="checkbox"/> 20D18 24 Watt D Series LED				
																<input type="checkbox"/> 62D24 62 Watt D Series LED				

MOUNTING		FINISH	
<input type="checkbox"/> CCK-SV4	Aircraft Cable	<input type="checkbox"/> S	Silver
<input type="checkbox"/> SCK-SV4	Stem Mount	<input type="checkbox"/> B	Black
<input type="checkbox"/> (blank)	Surface Mount	<input type="checkbox"/> W	White
		<input type="checkbox"/> C	Custom

*** Specifications subject to change without notice.

COMPRESSED FABRIC DRUM - SURFACE OR SUSPENDED



SHOWN AS SUSPENDED

LED MODULE

- Static 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable 120V TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

SHADE

Poly cotton blend (kona finishes 100% cotton) laminated to styrene

CONSTRUCTION

18 GA steel chassis

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

- Surface
 - Cable (3 cable system, 50" adjustable)
 - Stem Mounting (25" stem, 45 degree swivel)
- *** Contact Factory for custom pendant lengths

ADDITIONAL SHADE DIMENSIONS

DRAWINGS SHOWN AS SUSPENDED

