

STEPS

VRSL/HRSL - wall mount

STANDARD FEATURES

- · Die-cast louvered aluminum faceplate
- · Available in two sizes
- · Prismatic tempered glass lens
- Galvanized steel and powder coated back box
- · Suitable for concrete or non insulated wall
- · Closed cell continuous neoprene gasket









SERIES	MODEL	LAMP	VOLT	LUMENS	CCT	CONTROL	COLOR	OPTIONS
HRLS	5000	10W/LED	120V	800	3000	ELV DIMMER	TAL = TEXTURED ALUMINUM	NLU = NON LOUVERED
VRLS		3W/LED]	300			TBK = TEXTURED BLACK	CLU = CURVED LOUVERED BT = Bluetooth sensor RD = Remote dimming
							TBZ = TEXTURED BRONZE	
							TWH = TEXTURED WHITE	
			İ	Ì				
ORDERING INFORMATION								
SERIES	MODEL	LAMP	VOLT	LUMENS	CCT	CONTROL	COLOR	OPTIONS

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

- 1. Programmable drivers at the PACE factory
- 2. Color tunable
- 3. Capable of remote dimming
- 4. Can be equipped with motion sensors for on/off functioning
- 5. Can be equipped with light sensors for dusk-to-dawn automatic on/off operation
- 6. Bluetooth commissioning sensor capability for Android and iOS

Although PACE has prepared the information contained in this document with all due care, PACE does not warrant or represent that the information is free from errors or omission. Whilst the information is considered to be true and correct at the date of publication, changes in circumstances after the time of publication may impact on the accuracy of the information. The information may change without notice and PACE is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.



STEPS

VRSL/HRSL - wall mount

SIZE


9.25"

MOUNTING

Wall mount

COLOR

Textured or smooth polyester powder coat finishes RAL colors available



HRSL

