

URBANICA

UAPT 1 - post top

STANDARD FEATURES

- · Two sizes 18" and 24" diameter
- · Die-cast aluminum arms and collar
- Die-cast aluminum globe fitter and four point "Twist and Lock" for ease of maintenance
- · UV-stabilized acrylic or polycarbonate globe
- · Type III and V glass refractor optics
- · Many optical options available
- Matching wall sconce or wall arm mount available









SERIES	MODEL	SIZE	LAMP	VOLT	GLOBE/BAND	LUMENS	CCT	CONTROL	COLOR	OPTIONS		
UAPT-1 = POST TOP	4000	S = 18" L = 24"	30W/LED	347-480UNV	OG = OPAL GLOBE CG = CLEAR GLOBE FG = FROSTED GLOBE OPG = OPAL POLYCARBONATE CPG = CLEAR POLYCARBONATE FPG = FROSTED POLYCARBONATE WB = WIDE BAND DB = DOUBLE SB = SINGLE CB = COLOR PB = PERFORATED	6530 6300 6075	5000K 4000K 3000K 5000K 4000K 3000K	0-10V DIM	TEXTURED FINISHES TAL=TEXTURED ALUMINUM TBK= TEXTURED BLACK TBZ=TEXTURED BRONZE TWH=TEXTURED WHITE	HSS=HOUSE SIDE SHIELD^3 WMB1=WALL MOUNT BRACKET WMB2= WALL MOUNT BRACKET POLE ARM MOUNTS PAM=POLE ARM MOUNT^^ PAM2/180=2 ARMS AT 180^ PAM2/180=2 ARMS AT 180^ PAM2/180=2 ARMS AT 180^ PAM3C/180=2 ARMS AT 180 WITH CENTER HEAD^ PAM3C/180=2 ARMS AT 180 WITH CENTER HEAD^ PAM3C/180=3 ARMS AT 120 WITH CENTER HEAD^ PAM3/120=3 ARMS AT 120 WITH CENTER HEAD^ PAM4/90=4 ARMS AT 90^ PAM5C/90=4 ARMS AT 90 WITH CENTER HEAD^ EM = Emergency Backup MS = Motion sensor BT = Bluetooth sensor RD = Remote dimming		
ORDERING INFORMATION												
SERIES	MODEL	SIZE	LAMP	VOLT	GLOBE /BAND	LUMENS	CCT	CONTROL	COLOR	OPTIONS		

 \land Please indicate pole dimensions when ordering / $\land \land$ APM mounts over 2 3/8" O.D. x 3" Tenon

Consult factory for voltage and other lamp options. Product specifications subject to change without notice.

- 1. Programmable drivers at the PACE factory
- 2. Color tunable
- 3. Capable of remote dimming
- 4. Can be equipped with motion sensors for on/off functioning
- 5. Can be equipped with light sensors for dusk-to-dawn automatic on/off operation
- 6. Bluetooth commissioning sensor capability for Android and iOS

Although PACE has prepared the information contained in this document with all due care, PACE does not warrant or represent that the information is free from errors or omission. Whilst the information is considered to be true and correct at the date of publication, changes in circumstances after the time of publication may impact on the accuracy of the information. The information may change without notice and PACE is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.



URBANICA

UAPT 1 - post top

SIZES


Small = 18" diameter Large = 24" diameter

MOUNTING

Post top or wall arm bracket

COLOR


Textured or smooth polyester powder coat finishes RAL colors available



Wall mount bracket detail

6.5

WMB-1 = wall mount bracket



Louver

SL = Stacked

HPL = High performance louver


Glass refractor Type III or V









WMB-2 = wall mount bracket











DB = DOUBLE BAND



SB = SINGLE BAND



Mounting Configurations



	W	Н	Α	В	EPA
Small	18.0"	19.0"	11.0"	18.0"	1.3
Large	24.0"	24.0"	13.0"	22.5"	1.95

Although PACE has prepared the information contained in this document with all due care, PACE does not warrant or represent that the information is free from errors or omission. Whilst the information is considered to be true and correct at the date of publication, changes in circumstances after the time of publication may impact on the accuracy of the information. The information may change without notice and PACE is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.