Fixture Number			
Project Title	Туре	Qty	
Comments			

CAMMAN

- White Acrylic Diffuser
- Horizontal Trim Bars, Perf Metal Top & Bottom Accents
- Solid Top & Bottom
- Wet Location, ADA
- Camman Express Available (All Sizes)

Dimensions and Lamping:

OW216-24 7"A x 24" B x 4" D x 12" MC Weight: 9 lbs.

LN LED: Nominal 25W, 1450 Delivered Lumens

OW216-36 7"A x 36" B x 4" D x 18" MC Weight: 12 lbs.

LN LED: Nominal 40W, 2650 Delivered Lumens

OW216-48 7"A x 48" B x 4" D x 24" MC Weight: 18 lbs.

LN LED: Nominal 55W, 3850 Delivered Lumens

LED Color Temperature:

35K 3500K **30K** 3000K **40K** 4000K

Control:

CLV Integral Power Supply, 0-10V Dimming to 1%

Voltage:

1 120V **2** 277V **MV** Multi-Volt

PRD

Diffusers:

WA Gloss White AcrylicWM Matte White Acrylic

Standard Finishes:

PAL	Aluminum	PBB	Brushed Brass	POR	Pure Orange (RAL 2004)
PNL	Nickel	PAB	Antique Brass	PYL	Traffic Yellow (RAL 1023)
PBR	Bronze	PHB	Hammered Bronze	PGR	Emerald Green (RAL 6001)
PLB	Light Bronze	PHC	Hammered Copper	PBL	Signal Blue (RAL 5005)
PMB	Medium Bronze	PHS	Hammered Silver	STBD	To Be Determined
PDB	Dark Bronze	PSG	Satin Gold		
PMW	Matte White	PPA	Patina		

Traffic Red (RAL 3020)

Premium Finishes:


Satin Black


BA	Brushed Aluminum	PB	Polished Brass
SN	Satin Nickel	AB	Antique Brass
PC	Polished Chrome	PTBD	To Be Determined
BB	Brushed Brass		

Other Options:

REM Remote Emergency Power Supply

OW216 | Albany I





Notes:

- Custom sizes and finishes available upon request.
- Camman reserves the right to make design changes without prior notice.
- Mounting is to a 4 inch octagonal junction box.
- Photometric information is available at cammanlighting.com