Fixture Number			
Project Title	Туре	Qty	
Comments			

- White Acrylic Cylinder Diffuser & Bottom Lens
- Top & Bottom Metal Rings
- Center Stem to 45° Swivel Canopy
- Chain Hung Option Available

Dimensions and Lamping:

C505-8 12"A x 16"B x 8"C Weight: 10 lbs.

LN LED: Nominal 15W, 1450 Delivered Lumens

C505-10 14"A x 18"B x 10"C Weight: 16 lbs.

LN LED: Nominal 15W, 1500 Delivered Lumens

LED Color Temperature:

35K 3500K **30K** 3000K **40K** 4000K

Control:

 $\textbf{CLV:} \qquad \text{Integral Power Supply, 0-10V Dimming to } 1\%$

CPC: Integral Phase Cut Dimming Power Supply (120V Only)

Voltage:

1 120V **2** 277V **MV** Multi-Volt

Diffusers:

WA Gloss White Acrylic WM Matte White Acrylic

Standard Finishes:

PAL	Aluminum	PSB	Satin Black	PRD	Traffic Red (RAL 3020)
PNL	Nickel	PBB	Brushed Brass	POR	Pure Orange (RAL 2004)
PBR	Bronze	PAB	Antique Brass	PYL	Traffic Yellow (RAL 1023)
PLB	Light Bronze	PHB	Hammered Bronze	PGR	Emerald Green (RAL 6001)
PMB	Medium Bronze	PHC	Hammered Copper	PBL	Signal Blue (RAL 5005)
PDB	Dark Bronze	PHS	Hammered Silver	STBD	To Be Determined
DDR	Oil Rubbed Bronze	DSG	Satin Gold		

Patina

Premium Finishes:

Matte White

BA	Brushed Aluminum	PB	Polished Brass
SN	Satin Nickel	AB	Antique Brass
PC	Polished Chrome	PTBD	To Be Determined

PPA

BB Brushed Brass

Hanging Options:


ST	Stem	СН	Chain Hung with Power Cord
Other	r Ontions:		

REM Remote Emergency Power Supply



C505 | Northampton





Notes:

- Custom sizes and finishes available upon request.
- Camman reserves the right to make design changes without prior notice.
- Mounting is to a 4 inch octagonal junction box.
- Photometric information is available at cammanlighting.com