

Date: _____ Customer: _____

Project: _____

Type: _____ Qty: _____



The name alone – Cloud – evokes the poetic nature of these creations, which, according to their maker, should convey ‘the feeling of freedom and eccentricity’. Their poetic character and great variety transform the fair-weather clouds CLOUD, into an atmospheric light sculpture. Its durable high-tech material can be sculptured to make each light unique. Standard lengths range up to 7m – with other forms and sizes individually made. The voluminous lamp is suitable for large rooms and has sound-softening features. The material is a multi refined polyester fleece which is virtually tear-proof, resistant to aging and is almost nonflammable.

Construction

Luminaire

Made from flexible, tear-free, flame-resistant and aging resistant polyester material.

Mounting Option

- Pendant - Mama Cloud

Classifications

- Ingress Protection – IP20
- Protection against contact with fingers and against foreign bodies
- No protection against water

Electrical Characteristics

LED Specification

Cree LED.

For Warm Dim, Tunable White and Full Color Tunable Options

Lumenetix Araya 5 LED module - 5 color chip array to stabilize coloring across full spectrum, with all 1640-8000K whites occurring fully on black body curve, maintaining 95CRI or better. Tight color consistency with Max 2 SSD.

LED Life

L80 greater than 50,000 hours.

Correlated Color Temperature (CCT)

- Available in 3000K, 3500K, and 4000K. For Pendant XL Warm Dim range 1800K-3000K, tunable white range 1650K-8000K, and fully saturated color is available
- CRI 80+ 95+(pendant only)

Light Distribution

Diffuse

Dimming

Various dimming options available




Ordering Codes


KUMAMA -	CLD _____ -	PL-	LED-	DF -	_____ -	_____ -	_____ -
TYPE	LENGTH	PENDANT LIGHT	LAMPING	LIGHT DISTRIBUTION	CCT*	CRI	DIMMING
MamaCLD- Mama Cloud	70 – (2M) 6'-6 7/10" 72 – (3M) 9'-10 1/10" 74 – (4M) 13'- 1 5/10" 76 – (5M) 16'-4 8/10" 78 – (6M) 19'-8 2/10" 80 – (7M) 22'-11 6/10"	PL- Pendant light	LED- LED	DF – diffuse	27 – 2700K 30 – 3000K 40 – 4000K WD – warm dim TW - Tunable white CT – full color tunable	80 – 80+ min CRI 95 – 95+ CRI (for WD, TW, CT)	D1 – Triac Phase Dim (120v) D2 – -0-10V dim (10%) D3 – Lutron Hi-Lume dim to 1% (consult factory for 2-wire, 3-wire, or digital control) D4 – EldoLED 0% dim to dark

Ordering Example: **KUMAMA-CLD74-PL-LED-DF-30-80-D2**

70 - 6'-6 7/10"



80 - 9'-10 1/10"




74 - 13'- 1 5/10"



76 - 16'-4 8/10"



78 - 19'-8 2/10"




80 - 22'-11 6/10"




ADA COMPLIANT

Tunable White


Technical




Mama Cloud - CLD70




Mama Cloud - CLD72




Mama Cloud - CLD74



Mama Cloud - CLD76



Mama Cloud - CLD78



Mama Cloud - CLD80




ADA COMPLIANT




Mounting/Installation

Suspension



Name	Length	Width	Net Weight	Number of Suspensions
MAMACLOUD-70 LED	2 m	107	33lbs	2
MAMACLOUD-72 LED	3 m	163	44lbs	3
MAMACLOUD-74 LED	4 m	214	55lbs	4
MAMACLOUD-76 LED	5 m	287	66lbs	6
MAMACLOUD-78 LED	6 m	321	77lbs	6
MAMACLOUD-80 LED	7 m	394	88lbs	8

Assembly



Photometry — for full photometry, please reference IES files on www.kreon.com

KUMAMA-CLD-76-PL-LED-DF-30-80

MAMA CLOUD 5m @3000K

CRI:80+

power: 280W

Efficacy: 30375lm/W

