

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

AAL ARMS

SPECIFICATIONS

CONSTRUCTION


- The arm shall be of one piece unitized aluminum construction, fully welded and assembled. The back plate shall be one piece cast aluminum. The arm shall be prewired with a quick connector for easy installation.
- The arm shall have a cast aluminum fitter welded to the top of the arm(s) for attaching the fixture. The fixture shall be mounted with three stainless steel bolts through the top of the arm fitter into the fixture. The attachment point shall have a silicone pad for sealing the fixture to arm connection.
- Mounting hardware and J-box by others.


ORDERING GUIDE

Example: WMA22D-BLT CATALOG


Arm		Color	
WMA22U	Mount up. Weight: 5 lbs.	BLS	Black Gloss Smooth
WMA22D	Mount down. Weight: 4 lbs.	BLT	Black Matte Textured
		DBS	Dark Bronze Gloss Smooth
		DBT	Dark Bronze Matte Textured
		GTT	Graphite Matte Textured
		LGS	Light Grey Gloss Smooth
		LGT	Light Grey Matte Textured
		PSS	Platinum Silver Gloss Smooth
		VGT	Verde Green Matte Textured
		WHS	White Gloss Smooth
		WHT	White Matte Textured
		Color Option	
		CC 1	Custom Color


DIMENSIONS





WMA22U Note: Back plate is welded to the arm.





WMA22D Note: Back plate is welded to the arm.

Notes: 1 Consult factory for custom color, marine and corrosive finish

Current 🗐

currentlighting.com/aal

© 2022 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions. Page 1 of 1 Rev 06/01/22 aal_wma22ud_spec_R01

