

PURSUIT

FEATURES

- Sections can be joined for runs up to 150' with seamless lens
- Electrical Connections IP68 rated
- Symmetric, Asymmetric, Wall Graze & Wall Wash Distributions
- "L", "T" & "X" Illuminated connectors for custom shapes
- Output up to 1,000 lm/ft in each direction
- Fixed arm, adjustable arm, pendant, wall & mullion mounting options



Pursuit Down Light RND

RELATED PRODUCTS

[ØRND](#)

[ØRNI](#)



See Certification Specifications

ORDERING GUIDE

Example: RNLTX-L-ID-5-3K8-DL-UNV-BLT

CATALOG #




HOUSING

RNLTX		Light Engine		Lumen Output		CCT/CRI		Shielding		Voltage		Finish	
RNLTX-L	Pursuit L shape illuminated connector	D	Direct (Down)	5	500 lumens/ft	3K8	3000K, 80 CRI	DL	Diffuse lens - Down Only	UNV	120-277V	BLS	Black Gloss Smooth
		ID¹	Bidirectional (Up & Down Light)	7	750 lumens/ft	3K9	3000K, 90 CRI	CL	Clear lens			BLT	Black Matte Textured
RNLTX-T	Pursuit T shape illuminated connector	I¹	Indirect (Up Light)	10	1000 lumens/ft	35K8	3500K, 80 CRI					DBS	Dark Bronze Gloss Smooth
						4K8	4000K, 80 CRI			DBT	Dark Bronze Matte Textured	GTT	Graphite Matte Textured
RNLTX-X	Pursuit X shape illuminated connector					4K9	4000K, 90 CRI			LGS	Light Grey Gloss Smooth	LGT	Light Grey Matte Textured
						5K8	5000K, 80 CRI			PSS	Platinum Silver Gloss Smooth	VGT	Verde Green Matte Textured
										WHS	White Gloss Smooth	WHT	White Matte Textured
										Color Option		CC²	Custom Color




ACCESSORIES

Illuminated Connectors
(Enables Custom Shapes)

- RNLTX-L L shape
- RNLTX-TT shape
- RNLTX-XX shape



Connectors for the RND, Bidirectional (Up and Down) and RNI (Up)



Connectors for the RND, Direct (Down)

¹ The top of the connectors are not lit. Both sides connects are not lit for the up configuration.
² Consult factory for custom color, marine and corrosive finish options.