Odessa 2 Medium Double Side Cluster Column






6x27w LED 6x2005 Lumens

IP65 Suitable for wet locations

IKO4 Impact Resistant [Vandal Resistant]

Weight 20 lbs

POLE NOT INCLUDED



Construction

Aluminum Casting

Less than 0.1% copper content – Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength, clean detailed product lines and excellent heat dissipation.

Pre paint

8 step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

<u>Memory Retentive -Silicon Gasket</u> Provided with special injection molded "fit for

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets. Maintains the gaskets exact profile and seal over years of use and compression.

Thermal management

LM6 Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000 hours.

Surge Suppression

Standard 10kv surge suppressor provided with all fixtures.

Finishing

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence.

Paint

UV Stabilized 4.9Mil thick powder coat paint and baked at 200 Deg C.

This process ensures that Ligman products can withstand harsh environments. Rated for use in natatoriums.

<u>Hardware</u>

Provided Hardware is Marine grade 316
Stainless steel

Anti Seize Screw Holes

Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

Crystal Clear Low Iron Glass Lens

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge.

Optics & LED

Precise optic design provides exceptional light control and precise distribution of light. LED CRI > 80

<u>Lumen - Maintenance Life</u>

L80 /B10 at 50,000 hours (This means that at least 90% of the LED still achieve 80% of their original flux)

Stylish adjustable projector range.
Naturally beautiful and unique contemporary family,
Odessa packs a punch with an abundance of options
and accessories.

The Odessa family of floodlights have a modern aesthetic design and are available as a surface mounted floodlight cluster with adjustable pole clamp settings. Each individual floodlight can be specified with different beam distributions, as well as wattages if necessary to provide the perfect lighting solution for any environment.

The floodlights can be aimed in different directions to highlight specific features or elements in the environment, as well as provide security when illuminating dark areas on campuses and parks. This small and medium range of high performance LED floodlight luminaires provides a robust design for demanding applications such as; recreational areas, public spaces and architectural structures.

The luminaire has integrated heat sinks to facilitate LED cooling, as well as an integral driver. The Odessa is available in Narrow, Medium, Wide and Very Wide light distributions. Color temperature 2700K, 3000K and 4000K. Luminaire has optional accessories, such as visors, louvres and linear spread lenses.

The Odessa Cluster is highly flexible and lends itself to custom configurations.

For non standard fixture variations, as well as specific reflector requirements and dichroic filters, please contact the factory.

- The Odessa floodlight is available as an event pole attachment see Odessa Cluster.
- The fixture quantity, type and configuration is flexible, please contact factory for more options.

Additional Options (Consult Factory For Pricing)










A80131 Anti Glare Visor

A80231 Anti Glare Louv

A80114 Linear Spread

UOD-50021 GOBO Projecto





PROJECT DATE QUANTITY TYPE NOTE ORDERING EXAMPLE || UOD-21014 - 6x27w - VN - W30 - 03 - 120/277v UOD-21014 LAMP **LED COLOR FINISH COLOR VOLTAGE BEAM** 120/2**77**v 6x27w LED VN - Very Narrow 8° W27 - 2700K 01 - BLACK RAL 9011 6x2005 Lumens W30 - 3000K 02 - DARK GREY RAL 7043 Other - Specify W35 - 3500K 03 - WHITE RAL 9003 W40 - 4000K 04 - METALLIC SILVER RAL 9006 05 - MATTE SILVER RAL 9006 06 - LIGMAN BRONZE 07 - CUSTOM RAL ADDITIONAL OPTIONS DIM - 0-10v Dimming A80114 - Linear Spread Lens NAT - Natatorium Rated A80231 - Anti Glare Louvre A80131 - Anti Glare Visor * Anti Glare Visor, Anti Glare Louvre and Linear Spread Lens can't be combined, choose one [See below for GOBO ordering information] A GOBO projector can be added to any cluster column. List of GOBO options can be found below. Beam selection to the right. Please consult factory for pricing. **GOBO BEAM** N - Narrow 12° M - Medium 18° W - Wide 32° Custom laser cut GOBOs and glass colored GOBOs also available. Consult factory for more information

















Custom- 1 Color Glass Gobo- E Size

Custom- 2 Colors Glass Gobo- E Size

Custom- 3 Colors Glass Gobo- E Size

Custom- 4 Colors Glass Gobo- E Size

Custom- Black & White Glass Gobo- E Size



Odessa Product Family



- UOD-80001-21w-1688lm
- UOD-80002-11w-816lm



• UOD-80012-27w-2005lm



- UOD-50001-21w-1688lm
- UOD-50002-11w-816lm



- UOD-50011-36w-3458lm
- UOD-50011-40w-3695lm · UOD-50011-43w-4042lm
- UOD-50012-27w-2005lm



• UOD-50021-45w-1184lm

- UOD-50051-21w-1688Im
- UOD-50052-11w-816lm



- UOD-50061-36w-3458lm
- UOD-50061-40w-3695lm • UOD-50061-43w-4042lm
- UOD-50062-27w-2005lm



• UOD-50031-45w-1184lm



- UOD-50071-21w-1688lm
- UOD-50072-11w-816lm



- UOD-50081-36w-3458lm
- UOD-50081-40w-3695lm
- UOD-50081-43w-4042lm
- UOD-50082-27w-2005lm



• UOD-50041-45w-1184lm





Odessa 2

- UOD-30011-3x36w-3x3326lm • UOD-30011-3x40w-3x3695lm
- UOD-30011-3x43w-3x4042lm • UOD-30012-3x27w-3x2005lm



Odessa 1

- UOD-21001-3x21w-3x1673lm
- UOD-21004-6x11w-6x816lm



- · UOD-21012-6x36w-6x3326lm
- UOD-21012-6x40w-6x3695lm
- UOD-21012-6x43w-6x4042lm
- UOD-21013-3x27w-3x2005lm • UOD-21014-6x27w-6x2005lm



Odessa 2

- UOD-21021-4x36w-3x3326lm [13']
- UOD-21023-4x36w-3x3326lm [20'] • UOD-21025-4x36w-3x3326lm [26']
- UOD-21026-4x28w-3x2005lm [13'] • UOD-21027-4x28w-3x2005lm [20']
- UOD-21028-4x28w-3x2005lm [26']



- UOD-30001-3x21w-3x1673lm
- UOD-30002-3x11w-3x816lm



Odessa 2

- UOD-21031-4x36w-3x3326lm [15']
- UOD-21033-4x36w-3x3326lm [22']
- UOD-21035-4x36w-3x3326lm [28'] • UOD-21036-4x28w-3x2005lm [13']
- UOD-21037-4x28w-3x2005lm [20']
- UOD-21038-4x28w-3x2005lm [26']



- · UOD-21002-6x21w-6x1673lm
- UOD-21003-3x11w-3x816Im

