LIGMAN LIGHTING USA

IP65 : Suitable for Wet Locations
IK10 : Impact Resistant (Vandal Resistant)

UPR-50491

Paragon onground uplight cylindrical LED

A range of small robust and compact round or square on-ground up-lights for outdoor lighting effects using energy saving LED's and metal halide lamps. Designed for use in squares, parks, residential and shopping areas. This product is excellent for illuminating sculptures, trees and landscape environments where in-ground product is not required. Optional colored diffuser, lenses, filters and louvres are available to control the light. The LED option has a High Powered LED's with long service life 60,000 - 80,000 hrs.
Low copper content corrosion resistant die-cast aluminum body. Integral control gear. All external hardware in stainless steel. Durable silicone rubber gasket and clear toughened glass. Anodized high purity aluminum reflector. The luminaire is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance.

Physical Data
Length: 7.32"
Height: 10.15"
Weight: 8.1 lbs

Lamp
☐ 40w - 2750lm - White - LED ⊛

Beam Angle (Please Specify)
☐ VN - Very Narrow Beam: 14 Deg
☐ N - Narrow Beam: 25 Deg
☐ M - Medium Beam: 40 Deg

LED Color (Please Specify)
☐ W27 - 2700K
☐ W30 - 3000K
☐ W40 - 4000K

Voltage (Please Specify)
☐ 120V
☐ 277V
☐ Other _____

Options (Please Specify)
Color (Please Specify)

☐ 01-Black - RAL 9011   ☐ 02- Dark Grey - RAL 7043
☐ 03-White - RAL 9003   ☐ 04 - Metallic Silver - RAL 9006
☐ 05-Matt Silver - RAL 9006   ☐ 07- Custom - RAL _____
☐ 06-Bronze - RAL 6014

01	02	03	04	05	06

Color filters are accessories and must be ordered separately.

☐ Red   ☐ Blue   ☐ Amber   ☐ Green
A50816   A50817   A50818   A50819

Lens/Accesories

☐ Linear Spread Lens   ☐ Prismatic Lens   ☐ Anti Glare Louvre   ☐ Visor
       A50814   A50815   A51021   A51231

7.32"

Top view

10.15"

7.08"
6.45"
2.16"
0.23"

Mounting detail

Ordering Example : UPR - 50491 - White-40w - N - W30 - 120v - Options

PROJECT: _____   DATE: _____

TYPE: _____ QUANTITY: _____ NOTE: _____

ETL
Intertek