

IP65: Suitable for Wet Locations

HARRIE HARRIN

63"-

47.24

9.88

IK10: Impact Resistant (Vandal Resistant)

LUMINAIRE SPECIFICATION

Tel: 503-645-0500 Fax: 503-645-8100 7144 NW Progress Ct Hillsboro, Oregon 97124

www.ligmanlightingusa.com

UTA-95361

Tango square pendant downlight HP LED

Tango pendant luminaire with a selection of beam distributions for various downward lighting requirements.

They are suitable for many applications such as; residential and pedestrian areas, shopping malls, parks and gardens, as well as commercial, historic or modern architectural interiors and exteriors. The luminaires have features such as long life, limited maintenance and constant lifetime performance.

The luminaires use a high quality LED source with low energy consumption and long service life 50,000-80,000 hours.

The luminaire is rated as class I with the high power LED integral driver. Low copper content die-cast aluminum housing and frame. Single cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Anodized high purity aluminum reflector

High power LED with three different beam distribution options in 2700K, 3000K and

Physical Data

Trim: 6.3" Height: 9.88" Weight: 10.1 lbs

Lamp

□ 30w - 2075lm - White - LED @

Beam Angle (Please Specify)

- □ N Narrow Beam: 14 Deg
- ☐ M Medium Beam: 24 Deg
- □ W Wide Beam: 40 Deg

LED Color (Please Specify)

- □ W27 2700K
- □ W30 3000K
- □ W40 4000K

Voltage (Please Specify)

□ 120V

Ø0.24"

- □ 277V
- □ Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011
- □ 03-White RAL 9003
- □ 02- Dark Grey RAL 7043 □ 04 - Metallic Śilver - RAL 9006
- □ 05-Matt Silver RAL 9006
 - □ 07- Custom RAL
- □ 06-Bronze RAL 6014



















- ☐ AC- Custom aircraft cable length _
- □ RPS- Rigid stem pendant with swivel mount for 4" square junction box mounting. Specify stem length _____
- □ RPR- Rigid stem pendant with swivel mount for 4" round junction box mounting. Specify stem length _____
- □ DIM 0 10v Dimming
- □ 20w HP LED Module




6.34

Mounting detail

Swivel Canopy Pendant Square- A90321



Swivel Canopy Pendant Round - A90421



DATE: _

NOTE:

