



LUMINAIRE SPECIFICATION

IP65 : Suitable for Wet Locations IK10 : Impact Resistant (Vandal Resistant)






Bottom view



Swivel Canopy Pendant Square- A90321



Swivel Canopy Pendant Round - A90421

Ordering Example : UTA - 95351 - White- 30w - N - W30 - 120v - Options



Tango cylindrical pendant downlight HP LED

Tango pendant luminaire with a selection of beam distributions for various downward lighting requirements.

They are suitable for many applications such as; residential and pedestrian areas, shopping malls, parks and gardens, as well as commercial, historic or modern architectural interiors and exteriors. The luminaires have features such as long life, limited maintenance and constant lifetime performance.

The luminaires use a high quality LED source with low energy consumption and long service life 50,000-80,000 hours.

The luminaire is rated as class I with the high power LED integral driver. Low copper content die-cast aluminum housing and frame. Single cable entry. Housing is treated with a chemical chromatized protection before powder coating, ensuring high corrosion resistance. Anodized high purity aluminum reflector

High power LED with three different beam distribution options in 2700K, 3000K and 4000K.

Physical Data

Length: 6.3"

Height: 9.81" Weight: 7.5 lbs

Lamp

□ 30w - 2075lm - White - LED

- Beam Angle (Please Specify)
- □ N Narrow Beam: 14 Deg
- □ M Medium Beam: 24 Deg
- □ W Wide Beam: 40 Deg

LED Color (Please Specify)

- □ W27 2700K
- □ W30 3000K □ W40 - 4000K

Voltage (Please Specify)

- □ 120V
- □ 277V
- Other

Options (Please Specify)

Color (Please Specify)

- □ 01-Black RAL 9011 🗆 03-White - RAL 9003 D 05-Matt Silver - RAL 9006 □ 06-Bronze - RAL 6014
- Dark Grey RAL 7043
- □ 04 Metallic Silver RAL 9006
- □ 07- Custom RAL



- □ F Frosted Lens
- □ AC- Custom aircraft cable length _ ft
- □ RPS- Rigid stem pendant with swivel mount for 4" square junction box mounting. Specify stem length _____ ft
- □ RPR- Rigid stem pendant with swivel mount for 4" round junction box mounting. Specify stem length _____ ft
- DIM 0 10v Dimming
- □ 20w HP LED Module



Intertek





Rev: 11/13

Ligman Lighting USA reserves the right to change specifications without prior notice, please contact factory for latest information. Due to the continual improvements in LED technology data and components may change without notice.

