

| Project:      |  |  |
|---------------|--|--|
| Fixture Type: |  |  |
| Location:     |  |  |
| Contact:      |  |  |

# Three-Light Bath & Vanity

Wall or ceiling mounted • Damp location listed PROGRESS LED



# **Description:**

Create harmony in a variety of environments with Balance's clean design and environmentally friendly architectural styling. Soft acrylic lens and a brushed nickel finish are highlights of the three-light Energy Star LED fixture. Fixtures can be wall or ceiling mounted. Can be installed vertically or horizontally. 3000K, 90+ CRI, 623 lumens per module (source).

### **Specifications:**

- Brushed Nickel (-09) (plated)
- Steel Construction
- White acrylic diffuser
- LED Module is replaceable (part # 93054049)
- · Clean design.
- · Environmentally friendly architectural styling.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- · Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting plate for outlet box included
- · 6" of wire supplied
- · ENERGY STAR® qualified

#### Performance:

| Number of Modules      | 3                                   |
|------------------------|-------------------------------------|
| Input Power            | 9w per module                       |
| Input Voltage          | 120 V                               |
| Input Frequency        | 60 Hz                               |
| Lumens/LPW (Source)    | 623/69.2 (LM-82) per module         |
| Lumens/LPW (Delivered) | 881.4/32.6 (LM-79)                  |
| CCT                    | 3000 K                              |
| CRI                    | 90 CRI                              |
| Life (hours)           | 60,000 (L70/TM-21)                  |
| FCC                    | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp        | -30 °C                              |
| Max. Operating Temp    | 30 °C                               |
| Warranty               | 5 year warranty                     |
| Labels                 | cCSAus Damp location listed         |
|                        | ENERGY STAR® qualified              |
|                        |                                     |

# P2093-0930K9

#### Images:



#### **Dimensions:**

Width: 16-3/4" Depth: 3" Height: 5"

H/CTR: 2-1/2" (mounted horizontal)

Glass Width: 2-1/8" Length: 15-11/16" Height: 5"



# Three-Light Bath & Vanity





# P2093-0930K9

# **Dimming Notes:**

P2093 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

# **Dimming Controls**

| Lutron  | Nova T     | NTELV-300      |
|---------|------------|----------------|
| Lutron  | Vierti     | VTELV-600      |
| Lutron  | Ariadni    | AYCL-153P      |
| Lutron  | Diva       | DVCL-153P      |
| Lutron  | Maestro    | MAELV-600      |
| Lutron  | spacer/sys | tem SPSELV-600 |
| Leviton | Renoir II  | AWRMG-EAW      |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.