

One-Light LED Mini-Pendant

 Ceiling cord mounted • Dry location listed **PROGRESS LED**


Description:

Inspired by beautiful glass forms commonly found in a science lab, Beaker has a heightened sense of modern industrial styling. The 9W LED source offers energy efficient and cost savings benefits, while the industrial-inspired design complements a variety of mid-century modern interior designs. The one-light woven cloth cord hung mini-pendant has half clear, half mirrored glass with a Polished Chrome frame.

Specifications:

- Polished Chrome (-15) (plated)
- Steel Construction
- Mirror/Clear glass cylinder, White acrylic Diffuser
- LED Module is replaceable (part # 93054049)
- Inspired by beautiful glass forms commonly found in a science lab.
- Heightened sense of modern industrial styling.
- Vessels are suspended from herringbone cloth cords.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	270/38.1 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Dry location listed ENERGY STAR® qualified

P5344-1530K9

Images:



Dimensions:

Diameter: 5"
Height: 11-7/8"
Overall Ht. W/Chain: 122"

Glass
Width: 3-15/16"
Length: 3-15/16"
Height: 925"
Glass 2
Width: 2-15/16"
Length: 2-15/16"
Height: 0-11/16"

P5344-1530K9

Dimming Notes:

P5344 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.