

One-Light Close-To-Ceiling

 Wall or ceiling mounted • Damp location listed **PROGRESS LED**


Description:

One-light LED square wall or ceiling mount fixture. The geometric panel glass has a textured glass diffuser and Brushed Nickel knobs.

Specifications:

- Brushed Nickel (-09) (plated)
- Steel Construction
- Textured glass diffuser, White acrylic diffuser
- LED Module is replaceable (part # 93053641)
- Brushed Nickel knobs.
- Replaceable LED module.
- Geometric glass.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1211/71.2 (LM-82)
Lumens/LPW (Delivered)	504.9/30.6 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

P2306-0930K9

Images:



Dimensions:

Square: 12"
Depth: 2-5/8"
Height: 12"
H/CTR: 6"

Glass
Width: 12"
Glass 2
Width: 5-13/16"
Length: 5-13/16"
Height: 0-1/2"

P2306-0930K9

Dimming Notes:

P2306 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron	Nova T	NTELV-300
Lutron	Vierti	VTELV-600
Lutron	Maestro	MAELV-600
Lutron	spacer/system	SPSELV-600
Leviton	Renoir II	AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.