

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light Wall Sconce W/HAL AC LED Module

Wall mounted • Damp location listed PROGRESS LED





Description:

Enjoy Progress Lighting's version of a starry night with this LED wall sconce. The geometric panel glass has a Natural Brass diffuser and Architectural Bronze plate. This puts a beautiful light effect on the wall. The decorative shield features a pinhole pattern resembling a night sky and provides an unexpected and pleasing "twinkle" lighting effect. 90+ CRI, 3000K, 1,211 lumens 71.2 lumens/watt per module (source). Dimmable to 10% with ELV type dimmers. Can be wall mounted also.

Specifications:

- Architectural Bronze (-129) (painted)
- Steel Construction
- Brass (white painted backside) metal shade, Architectural Bronze (white painted backside) metal decorate shade
- LED Module is replaceable (part # 93053641)
- · Decorative shield features a pinhole pattern resembling a night sky.
- · Enjoy an unexpected and pleasing "twinkle" lighting effect.
- Available with a gently curved metal reflector for grazing effect or a glass diffuser for more general
- Beyond stands apart as a unique solution for lighting your home or business.
- 1,211 lumens 71.2 lumens/watt per module (source)
- · 3000K color temperature, 90+ CRI.
- · Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · Complies with "Americans with Disabilities Act" ADA
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1211/71.2 (LM-82)
Lumens/LPW (Delivered)	560/33.7 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

P7101-12930K9

Images:



Dimensions:

Square: 10-1/2" Depth: 3-5/8" Height: 10-1/2" H/CTR: 5-1/4"

Glass Width: 10-1/2" Height: 10-1/2" Glass 2 Width: 6-1/2" Height: 6-1/2"



One-Light Wall Sconce W/HAL AC LED Module





P7101-12930K9

Dimming Notes:

P7101 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron	Nova T NTELV-300
Lutron	Vierti VTELV-600
Lutron	Maestro MAELV-600
Lutron	spacer/system SPSELV-600
Leviton	Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.