LED

PROGRESS

Hide-a-Lite 3 120V LED Strips

Undercabinet

Туре	
-20	-30
P7002 🗌	
P7012 🗌	
P7005 🗌	
P7013 🗌	

				Total						
	Finish			System	Delivered	l	Dimensions (Inches)			
Catalog No.	Bronz	e White	Lamping	Wattage	Lumens	Dimmable*	Α	В	С	
P7002	-20	-30	2-LEDs	4.5w	157	No	3-1/2	9	1	
P7012	-20	-30	4-LEDs	6.5w	284	Yes	3-1/2	12	1	
P7005	-20	-30	6-LEDs	9w	425	Yes	3-1/2	18	1	
P7013	-20	-30	8-LEDS	12w	555	Yes	3-1/2	24	1	

Specifications:

<u>General</u>

- Direct wire and linkable with long life LEDs
- White baked enamel housing
- Extruded aluminum frame, polycarbonate end plates
- Tempered micro-prismatic glass lens

<u>Mounting</u>

- Flush mounted under cabinets and shelves, over a desk, in a kitchen or work area
- Keyhole slots on top for ease of mounting

<u>Electrical</u>

- 120V integral electronic driver rated for 35,000 hr. continuous use.
- On/Off rocker switch

<u>Lamping</u>

- Long life LEDs provide 70% lumen maintenance over 35,000 hours.
- 3000K (3050 \pm 150K) correlated color temperature
- 80 CRI
- No UV or Mercury

<u>Linking</u>

- Powered from a single location using the P8740 direct-wire junction box (each fixture can also be direct-wired individually)
- HAL3 linking cable accessories (P8735 (6"), P8733 (12"), P8737 (18"), P8738 (24"), P8743 (coupling cable to connect two linking cables together)
- Fixtures can be linked together to form a continuous row of illumination. (5 amps max.)
- Linking cables can be used with or without the use of the P8740 junction box

Dimming * (P7005, P7012 and P7013)

- Smooth and continuous dimming on most incandescent or ELV dimmer switches.
- Recommended Lutron dimmers: Diva DV-600P, Diva DVELV-300P, Skylark S-600P, Ariadni AY-600P, Ariadni TG-603P, Maestro MAELV-600
- Reference manufacturers' minimum load requirements for dimmer switches

<u>Labeling</u>

• UL-CUL damp location listed Rev. 11/13

Progress Lighting 701 Millennium Blvd. Greenville, South Carolina 29607