

| Project: | | |
|---------------|--|--|
| Fixture Type: | | |
| Location: | | |
| Contact: | | |

One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED





Description:

Arrive LED lanterns feature a die-cast aluminum, powder coated frame and heavily textured glass. One-light small wall lantern. 90+ CRI, 3000K, 623 lumens (source). Energy Star.

Specifications:

- · Black (-31) (painted)
- · Die-cast aluminum Construction
- Clear Seeded glass panels
- LED Module is replaceable (part # 93054049)
- · Die-cast aluminum, powder coated frame.
- · Heavily textured glass.
- · 90+ CRI, 3000K, 623 lumens. Energy Star.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- · Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- · 6" of wire supplied
- ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

| Number of Modules | 1 |
|------------------------|--|
| Input Power | 9w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 623/69.2 (LM-82) |
| Lumens/LPW (Delivered) | 396/49.5 (LM-79) |
| ССТ | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 60,000 (L70/TM-21) |
| FCC | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30 °C |
| Warranty | 5 year warranty |
| Labels | cCSAus Wet location listed |
| | ENERGY STAR® qualified |
| | Meets California Title 24 high efficacy requirements |

for outdoor use only

P6067-3130K9

Images:



Dimensions:

Width: 6" Depth: 7-3/8" Height: 8-3/4" H/CTR: 4"

Glass Width: 0-1/8" Length: 3-3/4" Height: 625"



One-Light Outdoor



P6067-3130K9

Dimming Notes:

P6067 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.