

# Small Wall Lantern

#### Project:

Fixture Type: Location:

Contact:

Wall mounted • Wet location listed PROGRESS LED



### P5676-13630K9

Images:

The one-light wall lantern from the Belle LED Collection features nautical undertones and a cage reminiscent of industrial spaces that is ideal for both interior and exterior settings. This fixture is available in convertible ceiling/pendant and wall mount options.

### **Specifications:**

**Description:** 

- Textured Graphite (-136) (powder coat paint)
- Aluminum Construction
- Etched glass diffuser
- · LED Module is replaceable (part # 93054049)
- Nautical undertones.
- Cage reminiscent of industrial spaces.
- Ideal for both interior and exterior spaces.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR<sup>®</sup> qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

### Performance:

Number of Modules	1	Width: 5 Depth: 7 Height: H/CTR:
Input Power	9w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	623/69.2 (LM-82)	
Lumens/LPW (Delivered)	401/50.9 (LM-79)	Glass Width: 2 Length: Height:
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 °C	
Max. Operating Temp	30 °C	
Warranty	5 year warranty	
Labels	cCSAus Wet location listed	
	ENERGY STAR <sup>®</sup> qualified	
	Meets California Title 24 high efficacy requirements	
	for outdoor use only	

### Dimensions:

Width: 5-1/2" Depth: 7-3/8" Height: 10-5/8" H/CTR: 3"

Glass Width: 4-3/8" Length: 4-3/8" Height: 8-3/4"



# Small Wall Lantern

Wall mounted • Wet location listed PROGRESS LED



## P5676-13630K9

#### **Dimming Notes:**

P5676 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

#### **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.