

# One-Light Outdoor

#### Project:

Fixture Type: Location:

Contact:

Images:

Wall mounted • Wet location listed PROGRESS LED



## P5723-8130K9

Get inspired with vintage undertones reminiscent of early 20th century train depots. This indooroutdoor LED Wall lantern is cast aluminum. 3000K, 90+ CRI, 1,211 lumens 71.2 lumens/watt per module (source).

### Specifications:

**Description:** 

- Antique Nickel (-81) (plated)
- Solid brass Construction
- · Antique Nickel, painted white inside metal shade, White acrylic Diffuser
- LED Module is replaceable (part # 93053641)
- Inspired by vintage light fixtures found in early 20th century train stations.
- + Solid brass construction with an Antique Nickle finish.
- Double arm attachment for stability.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR<sup>®</sup> qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

#### Performance:

| Number of Modules      | 1  |  |
|------------------------|--|--|
| Number of Wodules      | I  | Widt   |
| Input Power            | 17w  | Dept<br>Heig<br>H/C                                    |
| Input Voltage          | 120 V  |  |
| Input Frequency        | 60 Hz  |  |
| Lumens/LPW (Source)    | 1211/71.2 (LM-82)                                    |  |
| Lumens/LPW (Delivered) | 751/43.9 (LM-79)                                     | Glas:<br>Widt<br>Leng<br>Glas:<br>Widt<br>Leng<br>Heig |
| ССТ                    | 3000 K   |  |
| CRI                    | 90 CRI   |  |
| Life (hours)           | 60,000 (L70/TM-21)                                   |  |
| FCC                    | Meets FCC Title 47, Part 15 Class B                  |  |
| Min. Start Temp        | -30 °C   |  |
| Max. Operating Temp    | 30 °C  |  |
| Warranty               | 5 year warranty                                      |  |
| Labels                 | cCSAus Wet location listed                           |  |
|                        | ENERGY STAR <sup>®</sup> qualified                   |  |
|                        | Meets California Title 24 high efficacy requirements |  |
|                        | for outdoor use only                                 |  |



Width: 12" Depth: 13-1/4" Height: 12-1/4" H/CTR: 6-7/8"

Glass Width: 12" Length: 12" Height: 4" Glass 2 Width: 6" Length: 6" Height: 1"



# One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED



## P5723-8130K9

#### **Dimming Notes:**

P5723 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.