

ZX20


(includes former ZX20 and ZX20-SOi model)

ACCENT & LANDSCAPE | ZX20 Series | 2.75"
11W (960LM) | 120, 230V | SORAA, Halogen



FEATURES

- Larger round, directional 120V/230V PAR20 moder accent light for residential and commercial environments.
- Flexible lamp configurations include SORAA LED Lamp with patented Heat Sink or use your preferred LED or Halogen lamp.
- Wet Location Listed, IP67 Standard.
- Machined from solid aircraft grade (6061-T6), corrosion-resistant aluminum, then anodized and powder coated to create a highly durable, marine grade finish. Also available in solid brass or stainless steel.
- 240° vertical and 360° horizontal adjustment via locking swivel stem design.
- Field changeable optical lensing available.
- Available with adjustable Angled, Long, and Short Glare Shields and ground, surface, and canopy mounting options.
- Every fixture tested end of line for water tightness and light quality.
- Ships complete with selected accessories installed.



SORAA LED Standard Accent: ZX20-1R1SA-ABR

SPECIFICATIONS

Materials

Machined from billet 6061-T6 corrosion resistant aluminum with 304 stainless steel hardware. Available in 304/316 stainless steel or 360 brass upon request.

Finish

Aluminum materials are first anodized and then powder coated for a robust, marine grade finish. Stainless steel and brass models are provided with brushed surface.

Hood and Glare Shield

Weeping and Non-weeping Hood Styles. Set screw or threaded Angled, Short, or Long Glare Shields. (See page 4 for details)

Voltage

120V or 230V AC.

Wattage

Max. 11W for SORAA PAR20 lamp.

Light Engine

PAR20 Halogen lamp or PAR20 SORAA® LED lamp. Please refer to [SORAA PAR20](#) for lamp selection.

Dimming

Phase dimming, with trailing edge dimming preferable. Please refer to website for [SORAA PAR20](#) dimmer compatibility.

Lamp Base/Socket

Standard PAR20 E26 lamp base/socket.

Optics

Accepts up to 3 accessory pieces (hexcel louver, optical lenses, dichroic color filters, etc.). Secured in place with metal snap ring.

Mounting

Mounts using 1/2"-14 NPS male fitting compatible with all HK Lighting mounting accessories (See page 4 for details).

Listings

ETL Listed for Wet Location, IP67 Standard. RoHS Compliant.

ORDERING GUIDE

 EXAMPLE: **ZX20-1R1SA-ABL-120VNL-GSA-LVR-MJB-06-BRZ**

MODEL	PHYSICAL OPTIONS			MATERIAL / FINISH		LIGHT ENGINE	
ZX20							
ZX20 Series 2.75" Accent Light SORAA LED, LED Lamp or Halogen Lamp Low Voltage (PAR20)							
	TYPE	STYLE	HOOD	ABL Aluminum Black	VOLTAGE	LAMP	
	1R1 Line Voltage, Round Accent ¹	S Standard	A A Style: Weeping	ABR Aluminum Bronze	120V 120V AC (PAR20)	NL No Lamp ²	
			B B Style: No Weep Holes	AWH Aluminum White	230V 230V AC (PAR20)	SL SORAA Lamp Included ³	
			C C Style: Threaded, Weeping	AAC Aluminum Anodized Clear ¹		SN SORAA Lamp Not Included ³	
				NBR Natural Brass ¹		CC Custom Lamp Included	
				NCU Natural Copper ¹			
				NSS Natural Stainless Steel ¹			
				CCC Custom Finish ¹			

¹ Consult factory for specialty finish quoting and lead times

² Compatible with Halogen Lamp

³ Only compatible with SORAA LED Lamp

OPTIONAL INSTALLED ACCESSORIES

SORAA LAMP	GLARE SHIELD	OPTIC	MOUNTING (Most common listed, see Page 4 for additional options)
XXXXX SORAA LED Lamp Code	GSA A/B Glare Shield Angled	LVR Hexcel Louver	GROUND MOUNT
	GSL A/B Glare Shield Long	OSL Overall Spread Lens	MHJB-06-BRZ 6" Stainless Steel 3-Prong Spike (120-230V) Bronze
	GSS A/B Glare Shield Short	LSL Linear Spread Lens	MHJB-12-BRZ 12" Stainless Steel 3-Prong Spike (120-230V) Bronze
	CGSA C Glare Shield Angled	SOL Solite Soft Focus	JB-1 Brass In-ground Junction Box
	CGSL C Glare Shield Long	DCF Dichroic Filter	CANOPY MOUNT
	CGSS C Glare Shield Short		CM1-XXX 3.75" Square Canpy Plate
			CM3-XXX 4.75" Square Canpy Plate
			CM5-XXX 5" Round Canpy Plate
			CM5-2-XXX 5" Round Canopy Plate - Double
			SURFACE MOUNT
			CMLJ-XXX 2.7" Round Surface Box
			CB4.0-XXX 4" Round Surface Box
			CB5.5-XXX 5.5" Round Surface Box
			TREE MOUNT
			TM120-ABR Aluminum Tree Mount Box (120V)
			TM120-TS-ABR Stainless Steel Strap for TM125

• Consult Accessory Spec Sheet for desired option code.

• XXX represents color option.

ADDITIONAL ACCESSORIES (Not installed at time of order)


GLARE SHIELD ACCESSORIES

GSL-20-XXX	A/B Glare Shield Long
GSA-20-XXX	A/B Glare Shield Angled
GSS-20-XXX	A/B Glare Shield Short
CGSL-20-XXX	C Glare Shield Long
CGSA-20-XXX	C Glare Shield Angled
CGSS-20-XXX	C Glare Shield Short




OPTIC ACCESSORIES

LVR-20	Hexcel Louver
OSL-20	Overall Spread Lens
LSL-20	Linear Spread Lens
SOL-20	Solite Soft Focus
DCF-20	Dichroic Filter

PRODUCT DRAWINGS




ZX20-1R1S




OPTIONS & ACCESSORIES

HOOD OPTIONS




A-HOOD

Versatile hood with 8 weep holes for water drainage. Regressed lens for glare control. Suggested for general use or when fixture is aimed in an up position.



B-HOOD

Similar to A hood but without weep holes. Regressed lens for glare control. Used in an interior or down light application.




C-HOOD


Flush hood with machined threading on the outside for attachment of C-style glare shield, cleverly designed with hidden drainage channels.

OPTIONAL GLARE SHIELD

For use with A & B Hood,
fastened with Set Screw




For use with C Hood
fastened with Locking Ring




MOUNTING ACCESSORIES

Canopy Plate:




Fixture On CM5




CM2 CM1 CM3 CM5

Surface Mount Box:




Fixture On CB5.1




CMLJ CB4.0 CB4.0-SQ CB5.1 CB5.5 CB5.5-K/O

Ground Mount:




Fixture On MHJB-6




MHJB-6 MHJB-12 JB1

Tree Mount:




Fixture On TM120-TS




TM120-TS TM120-C-SM-HB TS-SO

Extension:



Fixture With EX,EL



EX EL T-BAR

Sign Light Arm: Please reference the Sign & Pole Mounting section in [Accessories](#) on our website.

Notes: