



CATALOG #: \_\_\_\_\_

Type: \_\_\_\_\_

PROJECT: \_\_\_\_\_

**FEATURES**

- Compact, low-profile design
- Available as full-time AC powered unit or emergency unit with battery backup
- EM unit provides 90 minutes of emergency operation
- Ultra-bright, energy-efficient, long-life LEDs in red or green
- Fully automatic solid-state two rate charger on EM units recharges battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- Unique design allows double face conversion in the field
- Removable directional indicators
- Custom message available
- Self-diagnostic option performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes
- Available on QuickShip

**SPECIFICATIONS**

- **HOUSING** – Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- **ELECTRICAL** – Dual 120/277 voltage standard. 4.8V long life, maintenance-free, rechargeable NiCd battery when specified with EM power option.
- **MOUNTING** – Mounting canopy for top or end mount. Universal knockout pattern on back plate for wall mount.
- **LISTINGS** –
  - UL 924 standard as an exit light suitable for dry or damp locations (0°C - +50°C).
  - Meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
  - Certified to CEC under Title 20 Regulations.
- **WARRANTY** – 5-year limited warranty.

**ORDERING EXAMPLE: EXIT - R - EM - WHT - AC - OPTIONS - D**

**ORDERING INFO**

SERIES	LETTER COLOR	POWER OPTIONS	HOUSING COLOR
EXIT	R Red G Green	AC AC operation EM AC operation with emergency battery backup	WHT Industry-standard white BLK Black

**OPTIONS**

COPY/SF	Custom message, single face <sup>[1]</sup>	VOLTAGE	D 120V/277V
COPY/DF	Custom message, double face <sup>[2]</sup>		
SALIDA	Salida faceplate <sup>[3]</sup>		
DC	Dual circuit <sup>[4]</sup>		
SDT	Self-diagnostic test <sup>[5]</sup>		
PC1	Polycarbonate shield <sup>[6]</sup>		
WG	Wireguard <sup>[7]</sup>		

**QUICKSHIP**

EXIT-R-EM-WHT-QS-D

**NOTES**

- <sup>1</sup> Consult factory.  
<sup>2</sup> Consult factory.  
<sup>3</sup> Industry-standard white only.  
<sup>4</sup> AC only.

- <sup>5</sup> EM only.  
<sup>6</sup> Ships separately. See page 2 for OPTIONS DETAILS.  
<sup>7</sup> Ships separately. See page 2 for OPTIONS DETAILS.

ELECTRICAL INFORMATION

	INPUT WATTS (W)	INPUT AMPS (A)
120V	3.8	0.034
277V	3.8	0.020

OPTIONS DETAILS

Ships separately.

PC1



DIMENSIONS: 13-3/16" x 9-3/16" x 2-1/2"

WG



DIMENSIONS: 13-3/4" x 15-1/4" x 6"