

# 4" LED Bi-Pin Retrofit Insert Baffle Trims



## Features

- Perfect for retrofitting Low Voltage Housings to LED.
- GU5.3 socket for MR16 retrofit.
- Baffle reduces stray light.
- Flicker free dimming.

## Specifications

<b>Wattage</b>	10W
<b>Lumens</b>	580 lm - 600 lm
<b>Voltage</b>	12V
<b>Color Temp.</b>	2700K, 3000K, 3500K, 4000K, 5000K - 4000K
<b>Dimmable</b>	Triac/ELV
<b>Lamp Type</b>	LED
<b>CRI</b>	90+
<b>Damp Location</b>	Listed

## Options



**EL140CT5W - 5CCT  
Switch**

## Technical Details

### Construction:


- Meticulously manufactured trim with a powder coated or anodized finish.
- Diecast trim ring for durability and lasting quality.
- Baffle helps reduce glare.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 4" Low Voltage IC and Non-IC versions with GU5.3 base.

**Dimmability:** Dimmability depends on transformer compatibility (magnetic or electronic).

## Dimensions



## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
<b>EL14030W</b>	LED	580 lm	3000K	10W	12V	Triac/ELV	White
<b>EL14040W</b>	LED	600 lm	4000K	10W	12V	Triac/ELV	White
<b>EL140CT5W</b>	LED	600 lm	2700K, 3000K, 3500K, 4000K, 5000K	10W	12V	Triac/ELV	White

## Product Number Builder Example: EL14030W

4" LED Bi-Pin Retrofit Insert	Color Temp.	Finish
<b>EL140</b>	<b>27 2700K</b>	<b>W White</b>

**30** 3000K  
**40** 4000K  
**CT5** 2700K - 5000K