



CYP8x28



CYP8x40



CYP8x52

## SPECIFICATIONS

### **Construction**

Fabric laminated to self extinguishing vinyl. Transparent fire retardant applied after fabrication. 40 standard fabric choices. Lumenart's standard material selection is subject to change based on supplier availability. It is common for material manufacturers to be out of stock for long periods of time, change or discontinue materials without notice based on market trends and/or material availability.

### **Mounting**

Mounts to octagon junction box or 4x4 junction box with round plaster adapter.

### **Suspension**

72" cord. Longer lengths available. 48" stem in 24", 12", 8" and 4" segments. Longer lengths available.

### **Bottom Shielding**

White Linen Bottom

### **Finishes**

Metal hardware is available in satin nickel, polished nickel, bronze and black

### **Electrical**

ETL listed dry location only. Specify 120 or 277v. Lamps by others.

### **Modifications**

Contact local representatives or factory for size, lamping, lens or finish modifications.

Use matrix below to order complete fixture

## ORDERING LOGIC

Family	Model	Lamping	Color	Volt	Finish	Suspension	Fabric	Fabric	Fabric	Fabric	Options***
CYP Cylinder Pendant	8" dia x 28" high	2xF14 T5 2xF24 T5HO LED 23w 2115lm	3000k 3500k LED 80-CRI	120v 277v	SN PN BZ BL	BC Black Cord MB Metal Braid Cord ST Stem	Linen White Cream Champagne Tan Celery Red Grape Green Apple Maize Chocolate Black	Silk Platinum Lt. Bronze New Copper Orange Black(opaque)	Raw Silk White Lt. Bronze Med. Bronze Gold Mineral Moss Amaretto Ginger Moonlight Claret Coffee Honey	TriLam** White Cream Antique Tan Brown Kona Green Grey Canary Red Orange Lapis Amber Spice Med. Grey Parsley	Dim ECO MK10 HiLum 0-10v  ALL FLUORESCENT DIMMING EXCEPT MK10 REQUIRE STEM SUSPENSION
	8" dia x 40" high	2xF21 T5 2xF39 T5HO LED 30w 2820lm									
	8" dia x 52" high	2xF28 T5 2xF54 T5HO LED 59w 5640lm									
<b>CYP</b>							Linen	Silk	RS	TL	

\*277 not available  
for GU24 or A19

\*\*Washable

\*\*\*not available  
for GR10q4  
or GU24

