

GOTHIC180


large

Arcluce Code

S-GO0223US-12A

Code Ref.

0869001A-730-12US



TECHNICAL INFORMATION

Light source: LED, 3000K, 16W, 1700lm, CRI>70

Light efficiency: 31lm/W

Power luminaire: 19W, 590lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Wiring: 120V 60Hz

Optic: two-way

Color: Black - 12

Weight: 38.14 lb

Size: A: 7" 3/32
B: 39" 3/8

IP66



IK10



1.94 ft²



Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Driver protected against voltage surges up to 4kV.
- Reflector made of 99,85 anodized aluminium with non-iridescent specular finishing.
- Screen made of 3/16" thermal-shock resistant tempered glass.
- Die-cast aluminium base (EN 47100).

Installation

- Double M20 cable gland for through wiring.
- Galvanized and painted steel base plate with galvanized steel stud bolts.

Note

- 2700K on request