

INGROUND25

trim above the ground





Arcluce Code

Code Ref.

O-IG0123US-30K

0767003C-830-30US



TECHNICAL INFORMATION	
Light source:	LED, 3000K, 2W, 220lm, CRI>80
Light efficiency:	90lm/W
Power luminaire:	2W, 180lm
LED life time:	> 60000h - L80 - B20 (Ta 25°C)
High colour consistency:	< 3 SDCM
Wiring:	ICC 700mA
Optic:	medium 22°
Color:	Stainless Steel - 30
Weight:	0.82 lb
Size:	A: Ø 1" 11/32 B: 3" 3/4 C: 4" 11/32

Appliance

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- Clear PMMA screen.
- 2200lb static load capacity.
- Can be walked over.

Installation

- Recessed installation.
- M12 AISI 316L stainless steel cable gland.
- Supplied with recessed installation box.
- Supplied with power cable (10').
- Recessed installation box made of engineering plastic or of AISI 316L stainless steel.
- AISI 316L STAINLESS STEEL FIXTURES SUITABLE FOR SUBMERGED INSTALLATIONS AT A MAXIMUM DEPTH OF 3'.

Note

- Amber color LED on request
- 2700K on request

IP68
40"

IK10

C UL US
LISTED

LB
2200