

INGROUND55

trim above the ground




Arcluce Code

O-IG1123US-30I

Code Ref.

0772005C-730-30US



TECHNICAL INFORMATION

Light source: LED, 3000K, 4W, 550lm, CRI>70

Light efficiency: 106lm/W

Power luminaire: 4W, 425lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

Wiring: ICC 350mA

Optic: medium 25°

Color: Stainless Steel - 30

Weight: 1.48 lb

Size:
A: Ø 2" 17/32
B: 3" 3/4
C: 4" 11/32

Appliance

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- Screen made of 3/16" thermal-shock resistant tempered glass.
- 2200lb static load capacity.
- Can be walked over.

Installation

- Recessed installation.
- M16 AISI 316L stainless steel cable gland.
- Supplied with recessed installation box.
- Supplied with power cable (10').
- Recessed installation box made of engineering plastic or of AISI 316L stainless steel.
- AISI 316L STAINLESS STEEL FIXTURES SUITABLE FOR SUBMERGED INSTALLATIONS AT A MAXIMUM DEPTH OF 3'.

Note

- 2700K on request

IP68
40"



IK08



LB
2200

