

INGROUND SHORT180

round trim above the ground




Arcluce Code

O-IG5153US-30S

Code Ref.

0761006D-830-30US



TECHNICAL INFORMATION

Light source: LED, 3000K, 12W, 1500lm, CRI>80

Light efficiency: 61lm/W

Power luminaire: 14W, 850lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Wiring: 120-277V 60Hz 0-10V

Optic: ultra wide flood 90°

Color: Stainless Steel - 30

Weight: 4.85 lb

Size:
A: Ø 7" 23/32
B: 4" 13/16
C: 5" 5/16

IP67



IK10



Appliance

- AISI 316L stainless steel body.
- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- White polyester powder painted steel reflector (10W FSQ version).
- Screen made of 13/32" thermal-shock resistant tempered glass.
- 4400-6600lb static load capacity.
- Can be driven over at maximum speed 12 mph.

Installation

- Recessed installation.
- Double M16 cable gland for through wiring.
- Supplied with recessed installation box.
- Supplied with power cable (2' 3" 9/16).
- Recessed installation box made of engineering plastic.
- UPON REQUEST FIXTURES CAN BE SUPPLIED WITH ANTI-SLIP GLASS.

Note

- Amber color LED on request