

# INGROUND-SHORT110

round trim flush with ground




Arcluce Code

**O-IG3243US-30I**

Code Ref.

**0770004C-830-30US**



## TECHNICAL INFORMATION

**Light source:** LED, 3000K, 4W, 500lm, CRI>80

**Light efficiency:** 108lm/W

**Power luminaire:** 4W, 430lm

**LED life time:** > 60000h - L80 - B20 (Ta 25°C)

**High colour consistency:** < 3 SDCM

**Wiring:** ICC 350mA

**Optic:** wide flood 47°

**Color:** Stainless Steel - 30

**Weight:** 1.9 lb

**Size:**  
A: Ø 4" 11/32  
B: 2" 11/16  
C: 7" 15/32

IP67



IK09



## Appliance

- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- AISI 316L stainless steel counter-ring.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Screen made of 5/16" thermal-shock resistant tempered glass.
- 4400lb static load capacity.
- Can be driven over at maximum speed 12 mph.

## Installation

- Recessed installation.
- Double M16 cable gland for through wiring.
- Supplied with recessed installation box.
- Supplied with power cable (10').
- Recessed installation box made of engineering plastic.
- FIXTURES WITH STAINLESS STEEL TRIM ARE SUGGESTED FOR WALK-OVER OR DRIVE-OVER APPLICATIONS.
- UPON REQUEST FIXTURES CAN BE SUPPLIED WITH ANTI-SLIP GLASS.

## Note

- Amber color LED on request

