

RAY-SHORT110

round trim stainless steel




Arcluce Code

H-RY3163US-30I

Code Ref.

0326005C-830-30US



TECHNICAL INFORMATION

Light source: LED, 3000K, 4W, 500lm, CRI>80

Light efficiency: 115lm/W

Power luminaire: 4W, 460lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Wiring: ICC 350mA

Optic: elliptic 10°X54°

Color: Stainless Steel - 30

Weight: 1.87 lb

Recessed hole: Ø 4"3/8

Size: A: Ø 4" 23/32
B: 2" 11/16

IP67



IK09



Appliance

- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Available on request: equipment wired for emergency lamp always lit - 1-3hours autonomy.
- PMMA lenses for LEDs.
- Screen made of 5/16" thermal-shock resistant tempered glass.

Installation

- Recessed installation.
- Double M16 cable gland for through wiring.
- Galvanized steel brackets.
- Supplied with power cable (10').

Note

- Amber color LED on request

