


Flagler B

POLES & BASES

Sample	FLBC	5	BBT
Ordering	<input type="text"/>	/ <input type="text"/>	/ <input type="text"/>
	A	B	C

DETAILS	A. MODEL																																	
	<p>FLBC Flagler B</p> <hr/> <p>B. POST SHAFT DIAMETER</p> <table border="0"> <tr><td>3</td><td>3"</td></tr> <tr><td>4</td><td>4"</td></tr> <tr><td>5</td><td>5"</td></tr> </table> <hr/> <p>C. COLOR</p> <table border="0"> <tr><td>BBT</td><td>basic black textured</td></tr> <tr><td>BMT</td><td>black matte textured</td></tr> <tr><td>WHT</td><td>white textured</td></tr> <tr><td>MBT</td><td>metallic bronze textured</td></tr> <tr><td>BZT</td><td>bronze textured</td></tr> <tr><td>DBT</td><td>dark bronze textured</td></tr> <tr><td>GYS</td><td>gray smooth</td></tr> <tr><td>DPS</td><td>dark platinum smooth</td></tr> <tr><td>GNT</td><td>green textured</td></tr> <tr><td>MST</td><td>metallic silver textured</td></tr> <tr><td>MTT</td><td>metallic titanium textured</td></tr> <tr><td>OWI</td><td>old world iron</td></tr> <tr><td>RAL</td><td>_____</td></tr> </table>	3	3"	4	4"	5	5"	BBT	basic black textured	BMT	black matte textured	WHT	white textured	MBT	metallic bronze textured	BZT	bronze textured	DBT	dark bronze textured	GYS	gray smooth	DPS	dark platinum smooth	GNT	green textured	MST	metallic silver textured	MTT	metallic titanium textured	OWI	old world iron	RAL	_____	<p>Construction: All cast aluminum parts shall be low copper alloy A356. All extruded aluminum parts shall be alloy 6061-T6, 6063-T5 or equal. Standard fluted shaft profile shall be 16-flat flutes for 3"OD and 12-flat flutes for 4", 5", & 6"OD.</p> <p>Base Covers: require specification of smooth or fluted shafts of the size required to meet wind load requirements</p> <p>Vibration Dampeners: Vibration dampener pads shall be provided when required by customer or deemed necessary by Beacon Products. Please consult factory for bridge mounted applications.</p> <p>EPA (effective projected area): EPA is defined as (projected surface area X drag factor) and measured in ft². Allowable post, luminaire arm, luminaire and accessory EPAs are derived from the most current published AASHTO (American Association of State Highway and Transportation Officials) standard, currently AASHTO 2001 (50yr design life). Customer assumes all responsibility for selecting the appropriate post for installation (consult factory for assistance). Luminaire arm, luminaire and accessory EPA must be equal to or less than allowable EPA of post. Consult a professional engineer for compliance with local codes and standards.</p> <p>Anchor Bolt: Anchor bolts, sized as required, double hex nuts and flat washers shall be hot dipped galvanized steel. A bolt circle template shall be provided for installation.</p> <p>Fasteners: All fasteners shall be Corrosion Resistant. When tamper resistant fasteners are required, spanner HD (snake eye) style shall be provided (special tool required, available at additional cost).</p> <p>Finish: Finish shall be a Beacote V polyester powder-coat electrostatically applied and thermocured. Beacote V finish shall consist of a five stage iron phosphate chemical pretreatment regimen with a polymer primer sealer, oven dry off, and top coated with a thermoset super TGIC polyester powder coat finish. The finish shall meet the AAMA 605.2 performance specification which includes passing a 3000 hour salt spray test for corrosion resistance and resists cracking or loss of adhesion per ASTM D522 and resists surface impacts of up to 160 inch-pound.</p> <p>Limited Warranty: Beacon Products warrants its products, to the original purchaser, against defects in materials and workmanship for proper usage for a period of 5 years after date of production, when properly installed, maintained and appropriately specified.</p>
3	3"																																	
4	4"																																	
5	5"																																	
BBT	basic black textured																																	
BMT	black matte textured																																	
WHT	white textured																																	
MBT	metallic bronze textured																																	
BZT	bronze textured																																	
DBT	dark bronze textured																																	
GYS	gray smooth																																	
DPS	dark platinum smooth																																	
GNT	green textured																																	
MST	metallic silver textured																																	
MTT	metallic titanium textured																																	
OWI	old world iron																																	
RAL	_____																																	
Due to our continued efforts to improve our products, product specifications are subject to change without notice.																																		