LANDMARK S LED

Architectural Indoor

_	_		
لج	(12)	LED	7

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




FEATURES

- ADA Compliant
- Aluminum Mounting Pan & Reflector
- Constant Current at 350 Milliamps
- CSA Listed Dry Location For Wall Mounting
- Dimmable to <5%
- Dimmable With Either Triac or Electronic Dimmers
- Estimated 50,000 Hours Life (L70)
- LED Light Fixture
- Luminous White Acrylic Diffuser
- Mounts Directly to 4" Junction Box (By Others)
- Mounting Hardware Included
- Open Top & Bottom
- Over-Current, Over-Voltage, and Short Circuit Protection
- Steel Trim Accents w/ Matte Silver Powder Coat Finish
- UL Class 2 Driver Power Factor >.90,
- 120V 350mA Driver is Dimmable
- 277V 350mA Drivers Are Not Dimmable

LINE DRAWING

INF DRAWING NOT TO SCALE





FINISHES

Antique Copper Textured

Black



Antique

Silver



Textured

White



Matte

Silver





For RAL Colors & Custom Match -Contact Teron Lighting Inc.





LANDMARK S LED

Architectural Indoor

ક્ષ ઉ (ED 👯
----------------	------

tecturai	inaoor	
	_	

Fixture Core

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
LNDS - Landmark S L25.0-350mA - 25.0W @350mA Constant Current		120V - 120V 277V - 277V (50 / 60Hz)	Not Applicable
ORDER INFO			
LNDS Example ^	L25.0-350mA	120V - 120V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable DRDER INFO	AS - Antique Silver BT - Bronze Mist SM - Matte Silver	35K - 3500K Color Temp 40K - 4000K Color Temp 50K - 5000K Color Temp	Not Applicable
ORDER IN O			
Not Applicable	SM	30K	Not Applicable

PROD	SOURCE	30K SPECS		
PROD LNDS	L25.0	80 CRI Typ. 1615 LED Source Lumens 64.6 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Acrylic Diffuser	3027860	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004

