Architectural Indoor

ይ	(I)	LED	7

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	




FEATURES

- ADA Compliant
- Centered Over and Mounted to 4" J-Box (By Others)
- CSA Listed Dry Location For Wall Mount
- Dimmable to 10%
- Luminous White Acrylic Diffuser
- Mounting Hardware Included
- · Open Top and Bottom
- Optional Surge Protector
- Steel Fascia with Matte Silver Powder Coat Finish
- Steel Mounting Plate Mounts to Flat Surface

LINE DRAWING

LINE DRAWING NOT TO SCALI



FINISHES Antique Swedish Antique Bronze Matte Sand Copper Silver Mist Silver Steel Textured Textured Textured Black White Bronze For RAL Colors & Custom Match -**Contact Teron** Lighting Inc.





Architectural Indoor



PO#: COMMENTS:

PROJECT: TYPE:

#:

QTY:

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
TGR - Tiger	L12.0-LT350 - 12.0W LED Strips @ 350mA 2-Wire Trailing or Leading Edge Driver L12.0-ZE350 - 12.0W LED Strips @ 350mA Low Voltage 4-Wire Dimming Electronic Driver	120-277V (120-230V Dimmable For Most LT LED Drivers) (ZE 0-10V Drivers Are Dimmable From 120V - 277V)	Not Applicable	
ORDER INFO				
TGR	L12.0-LT350	100-277V	Not Applicable	
Fxample ^				

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
TCB	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Text Black BZ - Text Bronze TW - Tex White	35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused S - Surge Protector TBC - Perforated Steel Top & Bottom Covers TCV - Perforated Steel Top Cover
ORDER INFO			

Example '

PROD	SOURCE	30K SPECS		
TGR	L12.0	30K - 3000K Color Temp 1400 LED Source Lumens 116.7 LED Source Lumens Per Watt		
	L18.0	30K - 3000K Color Temp 1986 LED Source Lumens 110.3 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens	3040960	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM

Architectural Indoor



 PROJECT:

 TYPE:

 PO#:
 QTY:

 COMMENTS:

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER
TGR - Tiger	L18.0-LT500 - 18.0W LED Strips @ 500mA 2-Wire Trailing or Leading Edge Driver L18.0-ZE500 - 18.0W LED Strips @ 500mA Low Voltage 4-Wire Dimming Electronic Driver	120-277V (120-230V Dimmable For Most LT LED Drivers) (ZE 0-10V Drivers Are Dimmable From 120V - 277V)	Not Applicable
ORDER INFO			
TGR Example ^	L18.0-ZE500	100-277V	Not Applicable

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
ТСВ	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Textur Black BZ - Textur Bronze TW - Textu White	35K - 3500K Color Temp 40K - 4000K Color Temp	F - Fused S - Surge Protector TBC - Perforated Steel Top & Bottom Covers TCV - Perforated Steel Top Cover
ORDER INFO			
TCB	I AC	30K	

Example ^

PROD	SOURCE	30K SPECS		
TGR	L18.0	30K - 3000K Color Temp 1986 LED Source Lumens 110.3 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens	3040960	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004



Architectural Indoor



PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	·

Fixture Core

PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
TGR - Tiger	L18.0-ZE500 - 18.0W LED Strips @ 500mA Low Voltage 4-Wire Dimming Electronic Driver	347V (ZE 0-10V Drivers are Dimmable @ 347V)	Dimmable 0-10V	
ORDER INFO				
TGR Example ^	L18.0-ZE500	347V	Not Applicable	

Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
тсв	AC - Antique Copper AS - Antique Silver BT - Bronze Mist SM - Matte Silver (Standard) SN - Sand SW - Swedish Steel TB - Textured Black BZ - Textured Bronze TW - Textured White	35K - 3500K Color Temp 40K - 4000K Color Temp	S - Surge Protector TBC - Perforated Steel Top & Bottom Covers TCV - Perforated Steel Top Cover
ORDER INFO			

Example ^

PROD	SOURCE	30K SPECS		
TGR	L18.0	30K SPECS 30K - 3000K Color Temp 1986 LED Source Lumens 110.3 LED Source Lumens Per Watt		

REPLACEMENT PART	PART NO	NOTES
White Acrylic Lens	3040960	
		Don't see the configuration you are looking for? Call us today at (513) 858-6004

