


DATE _____ PROJECT _____ TYPE _____ QUANTITY _____

Linear Symmetric LED Luminaire

FEATURES

- Constant current luminaire
- Integral driver
- Fixed or adjustable mounting
- 80+ CRI



FIXTURE COMPONENTS INCLUDED:

L280W Fixture, integral driver, mounting clips

FIXTURE COMPONENTS REQUIRED:

32' or 12' Leader feed cable, jumper cables

CONSTRUCTION

- Extruded aluminum housing with aluminum end caps and 7/8" K.O.
- Injection molded acrylic optics
- Powder coated silver

ELECTRICAL

- 120-277V AC integral driver
- Continuous runs mounted end to end with no space between luminaires

ORDERING

| | | | | | | | | |
|-------|--|--|--|--|--|--|--|--|
| L280W | | | | | | | | |
|-------|--|--|--|--|--|--|--|--|

| PRODUCT | POWER | LENGTH | LED COLOR | CONTROL | OPTICS | AIMING | MOUNTING | ACCESSORY |
|---|--|---|---|---|--|---|---|--|
| L280W Linear Symmetric LED Luminaire | 07 7.6 W/ln ft 10 10.5 W/ln ft ¹ | 16 16¼" actual 24 24½" actual 36 36" actual 48 47¾" actual | W2 2700K W3 3000K W35 3500K W4 4000K | ND Non-Dim D 1%, 0-10V Dim S Lutron ECO 1% Soft On Fade To Black PEQ1 ² Lo Lutron Hi-Lume 1% EcoSystem with Soft On, Fade to Black LDE1 ² T Lutron Hi-Lume 1% 120V 2-Wire LTEA ² LD 5-series EcoSystem LED driver LDE5 ² | 15 15° frosted lens 30 30° frosted lens 60 60° frosted lens 90 90° frosted lens | F Fixed A Adjustable | H Horizontal mounting clips (standard, included) | BL External blade louver |

¹ High Power driven at 9.8 W/ln ft for Lutron drivers

²4ft max length for Lutron options

ADDITIONAL COMPONENTS

SPECIFY QUANTITIES

LFC-L280W-S32

32' leader feed cable
(Dim and Non-Dim only)

LFC-L280W-S12

12' leader feed cable
(for Lutron drivers)

JC-L280W-COILED

6" Coiled jumper cable

RATINGS & CERTIFICATION

- cETLus Listed, IP67 Rated
- Wet location Rated
- Made in the USA
- Average rated LED life of 50,000 hours @ 70% lumen output




LUMEN OUTPUT

| STANDARD 30° | 559 Lm/ft | 7.6 W/ft | 74 Lm/w |
|--------------|-----------|-----------|---------|
| HIGH 30° | 772 Lm/ft | 10.5 W/ft | 74 Lm/w |


WARRANTY 3 Year warranty

visit electrixillumination.com for details

PHOTOMETRY




15° Symmetric




30° Symmetric

DIMENSIONS



CABLES AND ACCESSORIES

EXTERNAL BLADE LOUVER Matte Black



LEADER FEED CABLE (ONE REQUIRED PER INSTALLATION)

LFC-L280W-S32 32' leader feed cable per LED feed.
Straight connector (for Dim, Non-Dim drivers only)

LFC-L280W-S12 12' leader feed cable per LED feed.
Straight connector (for Lutron drivers)

JUMPER CABLES (OPTIONAL)

JC-L280W-COILED 12" Coiled Jumper Cable for end to end feeds

