


BC7

1. BASE

2. COLOR


1. BASE



BC5-4 (Fits over a 4"/100mm round pole)

BC5-5 (Fits over a 5"/125mm round pole)


14"/350mm DIA x 24"/610mm high.
Two piece clamshell.



BC7-4 (Fits over a 4"/100mm round pole)


BC7-5 (Fits over a 5"/125mm round pole)

18"/460mm DIA x 30"/760mm high.
Two piece clamshell with a one piece upper collar.



ACBCR (Fits over a 4"/100mm round pole)


14"/356mm DIA x 18"/460mm high.
One piece cover with a two piece upper collar.



BC6-4 (Fits over a 4"/100mm round pole)


BC6-5 (Fits over a 5"/125mm round pole)

17"/430mm DIA x 13"/330mm high
Two piece clamshell.
*AAL poles configured with BC6 shall have hand
hole location at 18".



BC8-4 (Fits over a 4"/100mm round pole)

12"/305mm DIA x 36"/915mm high.
Two piece clamshell.



ACBCS (Fits over a 4"/100mm square pole)

14"/356mm square x 18"/457mm high.
One piece cover with a two piece upper collar.

SPECIFICATIONS

Two piece base covers are cast #356 aluminum that fit over standard 4"/100mm or 5"/125mm round poles. Covers are attached with stainless steel hardware. Consult your AAL catalog for complete details on round poles.

WARNINGS

Caution must be exercised in the selection of a design wind speed when the pole is to be installed in a special wind region (as indicated by the wind map) or in an area where wind speed is unpredictable.

AAL recommends consulting a local engineer when the pole is to be installed in an area that may be subject to extreme weather and exposure

Poles installed on structures such as buildings and bridges may be subjected to vibration, oscillations, and other fatigue effects which are not covered by the AAL warranty.

The use of banners or other appendages can severely affect the loading of a pole. No banner or other appendage should be attached to an AAL pole unless approved by AAL.

If the products are to be used on an existing foundation or on other structures, the customer assumes all responsibility for the structural integrity of the existing foundation, anchorage or structures and all the consequences arising therefrom.

2. COLOR

WH Arctic White	VBU Verde Blue
BL Black	CRT Corten
BLT Matte Black	MAL Matte Aluminum
DB Dark Bronze	MG Medium Grey
DGN Dark Green	AGN Antique Green
TT Titanium	LG Light Grey
WDB Weathered Bronze	RAL Premium Color
MDB Bronze Metallic	CUSTOM ** Contact Factory

JOB _____

TYPE _____

NOTES _____