

DB2 – Decorative Pole

TYPE

5" ROUND (RD) & FLUTED (FL) DECORATIVE BASE



DB2

1. BASE	2. POLE	3. OAH	4. COLOR	5. OPTIONS/ACCESSORIES				

MAXIMUM ALLOWABLE EPA (MPH)

1. BASE	2. POLE	3. OAH	SHAFT	WT	85	90	100	110	120	130	140	150
DB2	5R12-188	12' (3.7m)	5" RD x .188"	116	32.3	28.5	22.7	18.6	15.5	13.1	11.2	9.6
DB2	5R14-188	14' (4.3m)	5" RD x .188"	116	32.3	28.5	22.7	18.6	15.5	13.1	11.2	9.6
DB2	5R16-188	16' (4.9m)	5" RD x .188"	123	27.3	23.9	19.0	15.5	12.8	10.8	9.2	7.9
DB2	5R18-188	18' (5.5m)	5" RD x .188"	129	22.8	19.8	15.6	12.7	10.5	8.8	7.4	6.4
DB2	5R20-188	20' (6.2m)	5" RD x .188"	136	18.9	16.4	12.8	10.3	8.5	7.0	5.9	5.0
DB2	5R22-188	22' (6.8m)	5" RD x .188"	142	15.8	13.5	10.4	8.3	6.8	5.6	4.7	3.9
DB2	5R24-188	24' (7.4m)	5" RD x .188"	148	13.1	11.1	8.4	6.6	5.3	4.3	3.6	3.0
DB2	5R25-188	25' (7.7m)	5" RD x .188"	151	11.9	10.0	7.5	5.9	4.7	3.8	3.1	2.5
DB2	5R14-250	14' (4.3m)	5" RD x .250"	132	35.7	31.5	25.2	20.6	17.2	14.5	12.4	10.7
DB2	5R16-250	16' (4.9m)	5" RD x .250"	140	30.5	26.8	21.3	17.4	14.5	12.2	10.4	9.0
DB2	5R18-250	18' (5.5m)	5" RD x .250"	150	25.8	22.5	17.8	14.5	12.0	10.1	8.6	7.3
DB2	5R20-250	20' (6.2m)	5" RD x .250"	158	21.8	18.9	14.8	12.0	9.9	8.3	7.0	6.0
DB2	5R22-250	22' (6.8m)	5" RD x .250"	167	18.5	15.9	12.4	9.9	8.1	6.7	5.7	4.8
DB2	5R24-250	24' (7.4m)	5" RD x .250"	176	15.7	13.4	10.3	8.2	6.6	5.5	4.5	3.8
DB2	5R25-250	25' (7.7m)	5" RD x .250"	180	14.5	12.3	9.3	7.4	6.0	4.9	4.0	3.4
DB2	5F14-188	14' (4.3m)	5" FL x .188"	116	21.4	18.7	14.8	12.1	10.0	8.2	6.9	5.8
DB2	5F16-188	16' (4.9m)	5" FL x .188"	123	17.8	15.5	12.1	9.8	8.0	6.6	5.4	4.5
DB2	5F18-188	18' (5.5m)	5" FL x .188"	129	14.5	12.5	9.7	7.8	6.3	5.1	4.1	3.3
DB2	5F20-188	20' (6.2m)	5" FL x .188"	136	11.8	10.0	7.6	6.1	4.8	3.7	3.0	2.3
DB2	5F22-188	22' (6.8m)	5" FL x .188"	142	9.4	7.9	5.8	4.6	3.9	2.6	2.0	1.4
DB2	5F24-188	24' (7.4m)	5" FL x .188"	148	7.4	6.1	4.3	3.3	2.4	1.7	1.1	0.6
DB2	5F25-188	25' (7.7m)	5" FL x .188"	151	6.6	5.2	3.6	2.7	1.9	1.2	0.7	0.3

Note: Overall height is measured to top of pole.

2. COLOR

Standard Color

WH	Arctic White
BL	Black
BLT	Matte Black
DB	Dark Bronze
DGN	Dark Green
TT	Titanium
WDB	Weathered Bronze
MDB	Bronze Metallic
VBU	Verde Blue
CRT	Corten
MAL	Matte Aluminum
MG	Medium Grey
AGN	Antique Green
LG	Light Grey

Premium Color

SHK	Shamrock
SPP	Salt and Pepper
SFM	Seafoam
WCP	Weathered Copper
RAL	RAL 4 digit Color
CUSTOM	Custom Color

3. OPTIONS / ACCESSORIES

- AD5 (This adapter is to be used only with standard AAL arms and post top mount fixtures that slip over a 4" od pole. The AD5 is a cast aluminum adapter that slips into the arm or over a 5"/125mm O.D. pole.)
- FH (Flag holder. Specify location on pole)
- FS1 (Single weatherproof fuse holder. Fuse by others.)
- FS2 (Double weatherproof fuse holder. Fuse by others.)
- PCR (Low profile twist lock photocell receptacle with cast pole cap top. Secures to the top of the pole with three stainless steel set screws. Photocell by others.)
- RBC (Cast aluminum receptacle housing, integrally welded to the pole. Includes a NEC approved clear weatherproof cover. Does not include a receptacle or internal wiring.)

SPECIFICATIONS

Base shall be cast aluminum #356 alloy, free of any porosity, foreign materials, or cosmetic fillers. Base casting shall be heat treated to a T-6 condition, and of uniform wall thickness, with no warping or mold shifting.

WARNINGS

Caution must be exercised in the selection of a design wind speed when the pole is to be installed in a special wind region (as indicated by the wind map) or in an area where wind speed is unpredictable.

AAL recommends consulting a local engineer when the pole is to be installed in an area that may be subject to extreme weather and exposure. Poles installed on structures such as buildings and bridges may be subjected to vibration, oscillations, and other fatigue effects which are not covered by the AAL warranty. The use of banners or other appendages can severely affect the loading of a pole. No banner or other appendage should be attached to an AAL pole unless approved by AAL.

If the products are to be used on an existing foundation or on other structures, the customer assumes all responsibility for the structural integrity of the existing foundation, anchorage or structures and all the consequences arising therefrom.

CAUTION

Poles should never be erected without the luminaire installed.

Anchor bolts shall be hot dip galvanized steel. Six galvanized hex nuts and flat washers, and a bolt circle template shall be provided. Anchor bolts for poles 14 feet high or less are 3/4" x 24" x 3". Anchor bolt for poles more than 14 feet high are 1" x 36" x 4".

CERTIFICATION

Certified UL 1598 in accordance with Article 410 of ANSI/NFPA 70, National Electrical Code.

JOB _____

TYPE _____

NOTES _____



DB2 – Decorative Pole

TYPE

5" ROUND (RD) & FLUTED (FL) DECORATIVE BASE

DIMENSIONS

