


## FEATURES

- Sections can be joined for runs up to 150' with seamless lens
- IP66 Rated
- Light Engine is independently rated IP67
- Electrical Connections IP68 rated
- "L", "T" & "X" Illuminated connectors for custom shapes
- Output up to 1,000 lm/ft
- Fixed arm, adjustable arm, pendant, wall & mullion mounting options.



## ORDERING CODE



### 1. MODEL

RNLTX-LL shape  
 RNLTX-TT shape  
 RNLTX-X X shape

### 2. LIGHT ENGINE

D Direct (Down)  
 ID Bidirectional (Up and Down)

### 3. OUTPUT

5 500 lumens/ft  
 7 750 lumens/ft  
 10 1000 lumens/ft

### 4. COLOR TEMPERATURE

3K8 3000K, 80 CRI  
 3K9 3000K, 90 CRI  
 4K8 4000K, 80 CRI  
 4K9 4000K, 90 CRI  
 5K8 5000K, 80 CRI

Consult factory for additional CCT options.

### 5. SHIELDING

DL Diffuse lens - Down Only  
 CL Clear lens

### 6. VOLTAGE


UNV 120-277V

### 7. FIXTURE FINISH


**Standard Color**  
 BL Black  
 BLT Matte Black  
 DB Dark Bronze  
 GT Graphite  
 MG Medium Grey  
 TT Titanium  
 WH White  
 CUSTOM Custom Color

## DIMENSIONS


### INDIRECT/BIDIRECTIONAL



L Shape




T Shape




X Shape


### DIRECT



L Shape



T Shape



X Shape



ARCHITECTURAL AREA LIGHTING  
 17760 Rowland Street | City of Industry | CA 91748  
 P 626.968.5666 | F 626.369.2695 | www.aal.net  
 Copyright © 2018 October 18, 2019 10:28 AM

JOB \_\_\_\_\_  
 TYPE \_\_\_\_\_  
 NOTES \_\_\_\_\_