



LES Series

Surface-Mount AC Edge-Lit LED Exit Sign

Catalog Number	
Comments	Type

FEATURES

Application

The LES Series provides bright, even letter illumination in an energy-saving LED edge-lit exit sign configuration. AC only operation. Special Wording ("SW") option allows customizing the stencil field to convey important information.

Construction

Water-clear injection-molded acrylic EXIT plaque is available with clear, white or mirror backgrounds. High strength extruded aluminum trim available in six finishes. Exit face design in single or double face with red or green letters. Custom printed directional chevron arrows. Standard EXIT stencil with 6" letters and 3/4" stroke.

Installation

Mounts to standard electrical boxes up to 4" square via universal adaptor plate and mounting canopy assembly. All mounting hardware is fully concealed.

Illumination

Exit face illumination is provided by energy saving, long life red or green LEDs. Exceeds UL 924 requirements for brightness and uniformity.

Compliances

- UL 924 Listed
- NFPA 70
- NFPA 101
- CEC T20 Compliant

Warranty

5 years full



Ceiling Mount



Wall Mount



End Mount



Special Wording Option

ORDERING GUIDE

LES

Model	Mounting	Faces	Letter Color	Arrows	Finish	Operation	Options
C	Ceiling mount	S Single	R Red	X No arrows	N Satin Aluminum	A AC Only	SW See available special wording choices on page 3 ²
W	Wall mount	D Double ⁵	G Green	EXIT	W White		W White plaque background
E	End mount			R *Right arrow ³	C Chrome		M Mirror-plaque background ¹
				EXIT>	B Black		
				L *Left arrow ³	S Satin Brass		
				<EXIT	Z Dark Bronze		
				D Double arrows			
				<EXIT>			
				C **L/R arrows ⁴			
				<EXIT/EXIT>			

*not for use with double face models.

Use "C" L/R arrow designator

**Double face models only. Provides reversible right or left arrow indicator

1 For use with single face models only. Standard on double face models

2 Enter Special Wording choice on page 3 example: SW41. Special wording option not available with 8" letter plaque. Some special wording signs not available with directional arrows

3. Not for use with double face models. Use "C" L/R arrows designator

4. Double face models only. Provides reversible right or left arrow indicator

5. Not for use with wall mounted models



LES Series

Surface-Mount AC Edge-Lit LED Exit Sign

SPECIFICATIONS

Electronics

Available in AC only operation. All components mounted inside housing. Includes AC-on indicator and pre-stripped AC input pigtail leads.

AC Input: 120/277VAC, 60 Hz.

Operating Temperature Range: 20°C to 30°C (68°F to 86°F)


Power Consumption: (120/277VAC)

POWER CONSUMPTION


Model	Single Face	Double Face
Red AC Only	2.2 watts	3.4 watts
Green AC Only	2.5 watts	4.0 watts

* Wattage figures include LED lamps, transformer and electronics power requirements.


DIMENSIONS



Ceiling Mount



Wall Mount



End Mount



LES Series

Surface-Mount AC Edge-Lit LED Exit Sign

LES Series architectural surface-mounted LED edge-lit exit signs feature an option for standard or custom special-wording. The images below represent standard special-worded signs available for the LES Series. The artwork and silk-screening for the standard signs shown below were previously developed therefore pricing for these special-worded signs do not incur a setup charge. If your special-worded requirements do not appear on this page, please contact the factory to request your custom special-wording sign. Custom special wording signs incur a one time set-up charge for each development.

STANDARD SPECIAL WORDING SIGNS WITH DIRECTIONAL ARROWS



SW118



SW41 (Arabic/Exit)



SW13



SW10



SW69



SW11

STANDARD SPECIAL WORDING SIGNS WITHOUT DIRECTIONAL ARROWS



SW4



SW3



SW31



SW2

STANDARD SPECIAL WORDING SIGNS

Category	Special Wording Number	Description
EXIT	SW 2	NOT AN EXIT
	SW 142	EXIT (TEXT IS INVERTED)
	SW 144	EXIT (W/ WHEELCHAIR SYMBOL)
DO NOT ENTER	SW 3	IN USE
EVACUATION	SW 10	AREA OF REFUGE
	SW 11	AREA OF REFUGE WITH WHEELCHAIR SYMBOL
	SW 13	AREA OF RESCUE ASSISTANCE WITH WHEELCHAIR SYMBOL
	SW 48	STAIRS
	SW 149	AREA OF/ RESCUE
LABORATORY	SW 4	X-RAY IN USE
	SW 31	LASER IN USE
	SW 181	BEAM OFF
RESTROOM/FACILITIES	SW 118	HANDICAPPED (SYMBOL ONLY)
INTERNATIONAL EXITS	SW 41	ARABIC/ EXIT
	SW 69	SALIDA
	SW 165	SALIDA (INVERTED TEXT)
AREA/ALERTS	SW 178	EMERGENCY CALL STATION
	SW 180	ELEVATOR (NO CHEVRONS)

NOTE: Special worded signs do not meet letter size requirements of UL 924.