

INTERCEPT® FLOODLIGHT

Cat.#

Job

Type



HUBBELL
Outdoor Lighting

Approvals

SPECIFICATIONS

Intended Use:

Intercept is a superior high output, high efficiency LED flood light, featuring a unique optical design that virtually eliminates glare with minimal impact on performance. It is available in a variety of flood distributions for lighting applications such as general and security lighting for large areas, port and rail centers, airport apron lighting and interior or exterior sports.

Construction:

- Heavy duty die-cast aluminum housing
- Light engine is thermally isolated from driver components
- UV stabilized polyester powder paint finish
- Horizontal and vertical aiming

LED:

- Modular optical assemblies enable 3 unique performance packages
- 90K lumens, 880 Watts
- 60K lumens, 580 Watts
- 48K lumens, 440 Watts
- 3000K, 4000K, 5000K CCT
- 70, 80 or 90 CRI

Optical/Electrical:

- Four distributions to maximize performance: 2x2, 3x3, 4x4, 5x5
- -40°C TO 40°C operating temp range
- 20kA surge protection device standard
- 0-10V dimming driver standard, dimming leads must be extended for connection to control systems (CD option)
- 120-480V operation 50/60Hz
- Driver RoHS compliant and IP65

Installation:

- Heavy duty yoke mount secured with 3/4" bolt

Listings:

- IP66, Listed to UL1598 for use in wet locations
- Patent Pending

Warranty:


For more information visit:

<http://www.hubbellighting.com/resources/warranty/>


PRODUCT IMAGE(S)




* Visor shown does not come standard



Six Modules




Four Modules



Three Modules

DIMENSIONS



A	B	C	D	E	F	Weight	EPA
23.5"	28.3"	12.0"	15.6"	32.66"	26.32"	100 Lbs	4.2
597mm	719mm	305mm	401mm	812mm	668mm	45 Kg.	3.9 Ft. ²

CERTIFICATIONS/LISTINGS



ORDERING INFORMATION

SERIES	MOUNT	ENGINE-WATTS	CCT	DISTRIBUTION	VOLTAGE	CORD	CONTROL OPTIONS	OPTIONS
VFS Flood Sports Lighting	Y Yoke UMY Under Mount Yoke	63L-440 440W 84L-660 660W 126L-880 880W	3K7 3000K, 70 CRI 4K7 4000K, 70 CRI 5K7 5000K, 70 CRI 57K7 5700K, 70 CRI 4K8 4000K, 80 CRI 5K8 5000K, 80 CRI 57K8 5700K, 80 CRI 4K9 4000K, 90 CRI 5K9 5000K, 90 CRI 57K9 5700K, 90 CRI	2 2x2 3 3x3 4 4x4 5 5x5 AV Aviation Optics ¹	120 120V 208 208V 240 240V 277 277V 347 347V 480 480V	3C 3' Prewired SEOWA cord 6C 6' Prewired SEOWA Cord 12C ² 12' Prewired SEOWA Cord	CD Continuous dimming SWP SiteSync pre-Comm SWF SiteSync field-Comm NXWE NX Fixture Module DMX DMX/RDM	LGC Less Glare Control SF Single Fuse DF Double Fuse GL Glass Lens

ACCESSORIES (ORDER SEPARATELY)

ACCESSORIES	
VFSVISOR	Top Visor
93093927	Laser Aiming Assembly
93101964	Safety Cable
93096023	Intercept Slip-Fit Adapter
CONTROL ACCESSORIES	
SWUSB*	SiteSync interface software loaded on USB flash drive for use with owner supplied PC (Windows based only). Includes SiteSync license, software and USB radio bridge node
SWTAB*	Windows tablet and SiteSync interface software. Includes tablet with pre loaded software, SiteSync license and USB radio bridge node.
SWBRG	SiteSync USB radio bridge node only. Order if a replacement is required or if an extra bridge node is requested.

¹ Includes glass lens

² 12' cord is default option

* When ordering SiteSync at least one of these two interface options must be ordered per project.
+ If needed, an additional Bridge Node can be ordered.



Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • Phone: 864-678-1000

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

© 2019 HUBBELL OUTDOOR LIGHTING, All Rights Reserved • For more information visit our website: www.hubbelloutdoor.com • Printed in USA VIP-SPEC May 15, 2019 3:57 PM