

JOB _____ TYPE _____
NOTES _____ APPROVALS _____


FEATURES

- Unique swivel mount provides superior aiming without loosening over time
- Available in 3500K and 5100K standard CCT



Certifications



SPECIFICATIONS



Approx. Weight = 3.16 lbs.



ORDERING CODE

KLV217			
Fixture¹	Electrical Module	Fixture Finish	
	Source 3L 3 LEDs	Color Temperature 3K 3500K 5K 5100K	Aluminum BL Black DB Dark Bronze GR Verde Green

Fixture Options	Transformer Options	Mounting Options
<u>Barn Doors</u> BD215BL Black BD215DB Dark Bronze BD215GR Verde Green <u>Fixed Hood</u> FH215BL Black FH215DB Dark Bronze FH215GR Verde Green	Refer to 112V Above-Grade/In-Grade Transformers spec sheet http://www.kimlighting.com/products/transformers	Refer to 120 Volt Mounting Options Spec Sheet http://cdn.kimlighting.com/content/products/specs/specs_files/kl_120vmounting_spec.pdf for individual mounting options.

¹ U.S. PATENT D298,656

Kim Lighting reserves the right to change specifications without notice.

SPECIFICATIONS

Housing and Lens Frame:

- Die-cast low copper alloy (<0.6% Cu) aluminum.

Swivel:

- Die-cast aluminum with locking teeth and 1/2" solid brass NPT mount. Provides horizontal rotation independent of the threaded mount. Swivel locked by 1/4-20 stainless set screw. Clear anodized prior to powder coating for added corrosion resistance.

Gasketing:

- Silicone gaskets throughout.

Fasteners:

- Stainless steel.

Wiring:

- 6' No. 18-2 12 Volt cable with fork connectors.

Optical System:

- A total of 3 LED emitters configured in a rectangular array comprised together as a module. Available in 3500K and 5100K.

Driver:

- Constant current electronic driver. Available in 12V input. -40°F. starting temperature. All drivers are Underwriters Laboratories recognized.

Finish:

- Each luminaire receives a fade and abrasion resistant, electrostatically applied, thermally cured, triglycidal isocyanurate (TGIC) polyester powdercoat finish. Standard colors include (BL) Black, (DB) Dark Bronze, (GR) Verde Green.

Certifications and Listings:

- UL Listed to U.S. and Canadian safety standards for wet locations.

WARRANTY:


- For full warranty see <http://www.hubbellighting.com/resources/warranty>

OPTIONS

Barn Doors

BD215


Extruded aluminum, fully adjustable. Provides beam and glare control. Available in Black, Dark Bronze or Verde Green finish.



Fixed Hood

FH215

Formed .062" thick aluminum. Provides glare control. Available in Black, Dark Bronze or Verde Green finish.



Kim Lighting reserves the right to change specifications without notice.