

Specifications

- | | | | |
|---|--|--|---|
| A Serviceable extruded aluminum heat sink/housing | C Stainless steel end plates with interlocking tabs | F Constant current LED board | I Extruded aluminum driver housing and drivers |
| B Extruded acrylic beam shaping lens | D Rotation locking tab with locking set screw | G Conduit entry (one each end, conduit and connections by others) | J Supply conduit and connectors by others |
| E Aluminum side arm with adjustable mounting tab (fasteners by others) | H Driver/housing joiner screw (one per fixture) | | |

Housing and Optic Assembly:

Extruded aluminum heat sink/optic housing. Exterior heat sink anodized for maximum emissivity. Stainless steel end plates. Extruded acrylic refractive semi-diffuse asymmetric beam shaping lens. Extruded aluminum driver housing and removable cover.

Finish:

Optic assembly – bright anodized aluminum. Side arms and driver compartment – mill finish aluminum or painted semigloss white for natatorium option. Painted surfaces receive a 6-stage pretreatment process prior to electrostatically applied baked powder enamel. All hardware – stainless steel.

Mounting:

Lay-in installation, side arms with mounting tabs can be base or wall mounted (fasteners by others). Luminaires can be mounted individually or joined together to form a continuous row. Optical assembly aiming is adjustable and is fixed in position by rotation locking screws at each side arm. When

mounted in a continuous row, assemblies lock together allowing all in the row to be aimed together.

Fixture weight: 1.7 lb/ft (2.5 kg/m).

Electrical:

Use 90°C wire for supply connections. Integral electronic Class II drivers. For complete driver specifications, see website, reference document [MA-1303](#). Driver/wireway compartment includes one conduit entry at each end. Channel cover is removable for access to driver and wiring. Luminaires may be butted end-to-end (connectors by others) for through wiring. Optional #12 AWG prewired modular through wiring with quick connectors. Optional, compatible dimming controls (by others). See website for dimming compatibility and specifications.

Standard:

UL listed or CSA certified for damp locations. For natatorium use, specify **OP** or **PK** option. 5 year warranty, maximum ambient temperature 45°C (113°F).




Features

- Tunable White Now Available!
- Asymmetric distribution – uniform surface illumination
- Wide lateral distribution – no socket shadows
- Fully adjustable and lockable optic assembly
- Integral driver with optional pre-wired harness
- Low profile – allows smaller slot depth

Performance

Precisely extruded acrylic lens produces an asymmetric distribution ideal for illuminating ceilings evenly.

For LM79 and photometric reports, visit thelightingquotient.com



L90(10k) > 60,000 hrs.
@ 25°C per TM-21



To form a Catalog Number

S 3 1 5 - R - S - - - - -
1 2 3 4 5 6 7 8 9 10

Project: _____

Type: _____

1 Source

S = Solid state (LED)

2 Style

315 = Small linear concealed LED with integral driver

3 Length / Light Output / Power

ORDER CODE	LENGTH	LUMENS	INPUT WATTS	NUMBER OF LEDS	DRIVE CURRENT
R02G	2FT	982	7	72	175mA
R02L	2FT	1925	14	72	350mA
R02M	2FT	3731	27	72	700mA
R03G	3FT	1473	10	108	175mA
R03L	3FT	2887	20	108	350mA
R03M	3FT	5596	41	108	700mA
R04G	4FT	1964	14	144	175mA
R04L	4FT	3849	27	144	350mA
R04M	4FT	7461	54	144	700mA
R05G	5FT	2455	17	180	175mA
R05L	5FT	4812	34	180	350mA
R05M	5FT	9327	68	180	700mA
R06G	6FT	2946	20	216	175mA
R06L	6FT	5774	41	216	350mA
R06M	6FT	11192	82	216	700mA
R07G	7FT	3436	24	252	175mA
R07L	7FT	6736	48	252	350mA
R07M	7FT	13057	95	252	700mA
R08G	8FT	3927	27	288	175mA
R08L	8FT	7698	54	288	350mA
R08M	8FT	14923	109	288	700mA
R09G	9FT	4418	31	324	175mA
R09L	9FT	8661	61	324	350mA
R09M	9FT	16788	122	324	700mA

Based on 3500K/80+CRI. [Click here](#) for scaled performance table.

Note: Other drive currents are available, consult factory.

4 Mounting

S = Sidearms with mounting tabs

5 Finish

00 = Anodized optical housing/heat sink; mill finish brackets and driver enclosure; stainless steel luminaire hardware (natatorium use option is painted)

02 = For damp / natatorium use. Driver enclosure and mounting brackets finished semi-gloss white, optical housing/heat sink are bright anodized

6 Voltage

M = 120-277V Universal voltage input

K = 347V input

7 Option (See Accessories Section for specifications)

00 = No options

0K = Modular through-wire harness with quick connectors

0P = [Natatorium](#) use; side arms, driver box pretreated and painted semigloss white

PK = Natatorium use with through-wire harness

8 Destination Requirement

0 = UL listed or CSA certified for U.S.

J = UL listed or CSA certified for Canada

9 Color Temperature / CRI

827 = 2700K, 80+ CRI

927 = 2700K, 90+ CRI

830 = 3000K, 80+ CRI

930 = 3000K, 90+ CRI

835 = 3500K, 80+ CRI

935 = 3500K, 90+ CRI

840 = 4000K, 80+ CRI

940 = 4000K, 90+ CRI

Note: Additional CCT and CRI options are available; consult factory.

Tunable White CCT Option

[TWH](#) = Tunable White from 2700K through 6500K, 80+ CRI. Intensity and CCT controlled via two (2) separate 0-10V analog controls (by others). Additional controls options are available, consult factory.

RGBW - Consult factory.



10 Dimming**

00 = Non-dimming

TD = ERP forward phase or reverse phase (120V only), dimming range 100%-10% power, compatible controls by others

ZX = 0-10V analog dimming 120-277V or 347V input, dimming range 100%-1%, 0-10V controls by others

L2 = Lutron Hi-lume LTE 120V input only, dimming range 100%-1%, compatible 2-wire dimming controls by others (see note*)

EL = eldoLED SOLOdrive 120-277V input, 0-10V analog dimming 100%-0.1% power (controls by others)

ED = eldoLED SOLOdrive 120-277V input, dimming range 100%-0.1%, DALI controls by others

**Dimming range refers to % power input, % light output will vary.


Refer to Driver Information document [MA-1303](#)

elliptipar from The Lighting Quotient

114 Boston Post Road, West Haven, Connecticut 06516, USA
Voice 203.931.4455 • Fax 203.931.4464 • [thelightingquotient.com](#)

Adjustable Mounting Feet

The optical assembly is adjustable and lockable, in addition, the S315 is provided with mounting feet that can raise the optical assembly to achieve lower aiming angles.



Standard (low) position allows peak candlepower to be aimed as low as **15° above nadir (vertical).**

Middle position allows peak candlepower to be aimed as low as **10° above nadir (vertical).**

High position allows peak candlepower to be aimed as low as **5° above nadir (vertical).**

