
20 Linear Wall Wash Semi-Recessed

Plaster Trim






Ordering Information								
WG-20LWW	SRPT	S						
Model	Fixation	Pattern	Length	Power ¹	CRI/ CCT ²	Driver ³	Lens	Finish
WG-20LWW	SRPT	S	А	L M	927 930 935 940	X S D010 L3DAE L3D0E DFPN	OD (std) SD	W (std) B G F



Semi Recessed Plaster Trim (SRPT)



Gypsum Wall

Luminaire

- Continuous, evenly illuminated snap-in lens without visible LED pattern.
- Standard Opal Diffuser for even illumination and no LED appearance. Satin Diffuser for high efficiency and minimal LED appearance.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Lengths factory cut to exact field dimensions.
- Powder coat painted white RAL 9010.
- Supplied with 4' class 2 plenum rated feed cable per fixture lengths.

Fixation

■ SRPT = Semi Recessed Plaster Trim

Pattern

■ S = Straight run

Length

A = specify inches to the nearest 0.25" (i.e. 72.25")

Power¹

- L = 3.2W/ft low power (24V)
- M = 6.4W/ft mid power (24V)

CRI/CCT²

90+ CRI minimum (Low/Mid)

- 927 = 2700K (188/348 lm/ft)
- \blacksquare 930 = 3000K (194/359 lm/ft)
- 935 = 3500K (198/366 lm/ft)
- 940 = 4000K (200/370 lm/ft)

Driver (remote)³

- \blacksquare X = No driver, ordered separately
- S = Standard driver 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3D0E = Lutron Hi-lume Premier 0.1% EcoSystem, 120-277V
- DFPN = Lutron Forward Phase 1%, 120VAC

Lens

- OD = Satin opal diffuser (standard)
- SD = Satin clear diffuser (high efficiency)

Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

Emergency

- Emergency LED driver available, order separately (remote)
- 1 Wattage shown does not include power supplies/drivers.
- 2 Delivered lumens with satin opal diffuser shown.
- 3 Remote power supply required. See power supply page for details.

