Apache

Project: ______
Type:




Bollard & Pole | topLED 7 W | CRI 80 | 3000K | General Lighting | Dark brown | Wet location | 180mA $\,$



LL-E64264-W-00



Technical data		
Designer	Studio RIGO	
Туре	Bollard	
Installation position	Floor	
Installation environment	Outdoor	
Light Source	LED	
Optics	General Lighting	
Light emission direction	downward	
Power	7 W	
Operation	180mA	
Source lumens	1034 lm	
ССТ	3000 K	
Color rendering index	80 Ra	
Safety class	Class 2	
IP	IP65	
IK	IK08	
Glow wire test 850°		
Direct mounting on normally flammable surfaces Yes		
CE	Yes	
ETL	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission Single er		
Net weight	1,78 Kg	
Electrostatic discharge protection	4 KV	
Surge protection	0,5 KV	
Ordinary temperature on the glass	104 °F	



Finishing casing		
Material	Aluminum 6060	
Color	Dark brown	
Process	Open pore anodizing + Powder Coating	

Finishing diffuser	
Material	UV Resistant Polycarbonate
Color	opaline

Finishing base			
Material	Galvanised Iron		
Color	Dark brown		
Process	Powder coating		

Notes:			

Apache



35 %

1034 lm

367 lm

52 lm/W

3000 K

3 Step MacAdam

7 W

Bollard & Pole | topLED 7 W | CRI 80 | 3000K | General Lighting | Dark brown | Wet location | 180mA | Base

LL-E64264-W-00

Single emission bollard & pole for outdoor application. The warm white LED light source with a general lighting light distribution is composed of 4 powerled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 1034 lm, with a 147.7 lm/W nominal luminous efficacy.

The device body is made of aluminium 6060 and features a dark brown finish, processed by means of open pore anodizing + powder coating; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP65; the total weight is of 2.205 lbs.

The total absorbed power is 7 W.

and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Color rendering index 80 Ra LED Life / Failure Ratio L70 B20 C10 108000h (at Tj 65 Ta 25) OPTICAL Light distribution symmetry Symmetrical 2 C0/C180 optics 68°

This product contains a light source of energy efficiency class D.

Energy efficiency class

Light Output Ratio (LOR)

Led features

Source lumens


Power

Delivered lumens

Luminaire efficacy

Color temperature

Standard Deviation of Colour Matching



0.5	0.67	E(0°) E(C0)	34.0°	358
1.0	1.35	E(0°)	34.0°	0 89
1.5	2.02	E(0°)	34.0°	0 40
2.0	2.70	E(0°)	34.0°	22
2.5	3.37	E(0°)	34.0°	0 14
3.0 Distance [m]	4.05 Cone diameter [m]	E(0°)	34.0°	0

Apache

3/3



Apache | Bollard & Pole | Accessories LL-E64264-W-00

Anchor - Tie rods

installation position: floor, Cover material: aisi 304 steel

Code E64210

15.09.2022 inter•lux inter-lux.com/linealight